

Objectives

- More on using strings
- Computer's representations of data types
- **str** methods

Feb 13, 2008

Sprengle - CS111


1

Strings

- Actually a *sequence* of characters

➤ Example:

string = "The Beatles"



Feb 13, 2008

Sprengle - CS111

2

Iterating Through a String

- For each character in the string

string of length 11

```
for char in string:  
    print char
```

'T'	'h'	'e'	' '	'B'	'e'	'a'	't'	'l'	'e'	's'
0	1	2	3	4	5	6	7	8	9	10

An integer

```
for pos in xrange(len(string)):  
    print string[pos]
```

Index into the string

- For each position in the string

Feb 13, 2008

Sprengle - CS111

3

Substrings Operator []

- Look at a particular character in the string

➤ Syntax: `str[<integer expression>]`

➤ [Positive values]: index of character

➤ [Negative values]: count backwards from end

- Look at a sequence of characters in the string

➤ Syntax: `str[<start>:<end>]`

Feb 13, 2008

Sprengle - CS111

4

Testing for Substrings

- Using the **in** operator
 - Used **in** before in **for** loops
- Syntax:

```
substring in string
```

➤ Evaluates to True or False

- Example:

```
if "cat" in name:  
    print name, "contains 'cat'"
```

Feb 13, 2008

Sprengle - CS111

5

Representations of Data

- Computer needs ways to represent different types of data
 - Eventually, all boils down to 1s and 0s
- Computer needs to translate between what we know (**decimal, strings**) to what the computer knows (**binary**) and back again
- Seems like a divergence on strings but just wait...

Feb 13, 2008

Sprengle - CS111

6

Decimal Representations

- Decimal is base 10
- Digits: 0, 1, 2, 3, 4, 5, 6, 7, 8, 9
- Each *position* in a decimal number represents a power of 10

Feb 13, 2008

Sprengle - CS111

7

Decimal Representations

- Decimal is base 10
- Digits: 0, 1, 2, 3, 4, 5, 6, 7, 8, 9
- Each *position* in a decimal number represents a power of 10
- Example: 54,087

5	4	0	8	7
10^4	10^3	10^2	10^1	10^0

- $= 5*10^4 + 4*10^3 + 0*10^2 + 8*10^1 + 7*10^0$
- $= 5*10,000 + 4*1000 + 0*100 + 8*10 + 7*1$

Feb 13, 2008

Sprengle - CS111

8

Number Representations

Characteristic	Decimal	Binary
Base	10	2
Digits	0, 1, 2, 3, 4, 5, 6, 7, 8, 9	0, 1
Position represents	Power of 10	Power of 2

- Binary: two values (0, 1)
 - Like a light switch (either **off** or **on**) or booleans (either True or False)
- 0 and 1 are *binary digits* or **bits**
 - 64-bit machine: represents numbers (and other data) with 64 bits

Feb 13, 2008

Sprengle - CS111

9

Binary Representation

- Example: 1101

1	1	0	1
2^3	2^2	2^1	2^0

- $= 1*2^3 + 1*2^2 + 0*2^1 + 1*2^0$
- $= 1*8 + 1*4 + 0*2 + 1*1$
 - Decimal value: 13

- **Practice:** 10110

Feb 13, 2008

Sprengle - CS111

10

Binary Representation

- Example: 10110

1	0	1	1	0
2^4	2^3	2^2	2^1	2^0

- $= 1*2^4 + 0*2^3 + 1*2^2 + 1*2^1 + 0*2^0$
- $= 1*16 + 0*8 + 1*4 + 1*2 + 0*1$
 - 22

Generalize this process into an algorithm...

Feb 13, 2008

Sprengle - CS111

11

Algorithm: Converting Binary to Decimal

- **Accumulator design pattern**
- Read in the binary number as a string
 - The starting exponent will be the length of the string-1
- Initialize the result to zero
- For each bit in the binary number
 - Multiply the bit by the appropriate power of 2
 - Add this to the result
 - Reduce the exponent by 1
- Print the result

Implement algorithm
binaryToDecimal.py

Feb 13, 2008

Sprengle - CS111

12

Algorithm: Converting Decimal to Binary

- Read in the decimal as an integer
- Initialize the result to the empty string
- Repeat until the decimal is 0:
 - `result = str(decimal % 2) + result`
 - `decimal = decimal / 2`
- Print the result

Try out algorithm with 22

Implement algorithm
`decimalToBinary.py`

Feb 13, 2008

Sprengle - CS111

13

String Representations

- A **string** is a sequence of characters
- Each character is stored as a binary number
- **ASCII** (American Standard Code for Information Interchange) is one standard encoding for characters
 - One problem with ASCII is that it is based on the English language
 - Cannot represent other types of characters
- Unicode is a new standard

Feb 13, 2008

Sprengle - CS111 [ASCII Table Handout](#)

14

ASCII Questions

- Lowercase letters are represented by what range of numbers?
- Uppercase letters are represented by what range of numbers?
- What is the difference between the decimal encoding of 'M' and 'N'?
 - Between 'm' and 'n'?

Feb 13, 2008

Sprengle - CS111

15

ASCII Questions

- Lowercase letters are represented by what range of numbers?
 - 97--122
- Uppercase letters are represented by what range of numbers?
 - 65--90
- What is the difference between the decimal encoding of 'M' and 'N'?
 - Between 'm' and 'n'?
 - 1

Feb 13, 2008

Sprengle - CS111

16

Translating to/from ASCII

- Translate a character into its ASCII numeric code using **ord**
 - `ord('a') ==> 97`
- Translate an ASCII numeric code into its character using **chr**
 - `chr(97) ==> 'a'`

`ascii_table.py`
`ascii.py`

Feb 13, 2008

Sprengle - CS111

17

Encryption

- Process of encoding information to keep it secure
- One technique: Substitution Cipher
 - Each character in message is replaced by a new character

Feb 13, 2008

Sprengle - CS111

18

Caesar Cipher

- Replace with a character X places away
 - X is your key
- Julius Caesar used it to communicate with his generals
- “Wrap around”
- Write program(s) to do this in lab

Feb 13, 2008

Sprenkle - CS111

19

Caesar Cipher

- Using the ASCII handout, what would be the encoded messages?

Message	Key	Encoded Message
apple	5	
zebra	5	
the eagle flies at midnight	-5	

Feb 13, 2008

Sprenkle - CS111

20

Caesar Cipher

- What is your algorithm for the encoding process?
- How would you decode an encrypted message?

Message	Key	Encoded Message
apple	5	fuuqj
zebra	5	ejgwf
the eagle flies at midnight	-5	ocz zvbz agdzn vo hdyidbco

Feb 13, 2008

Sprenkle - CS111

21

Broader Issue: Electronic Voting

- Select from one of three articles
 - [The Risks of Electronic Voting](#)
 - [Princeton Scientists Create Vote-Stealing Program](#)
 - [Voting with \(Little\) Confidence](#)

Feb 13, 2008

Sprenkle - CS111

22