

Objectives

- Review: importing modules
- Intro to design patterns
- Definite loops

Jan 21, 2008

Sprenkle - CS111

1

Review: Python Libraries

- Python has a rich library of functions and definitions available for your use
 - The library is broken into **modules**
 - A **module** is a file containing Python definitions and statements
- To use a module's definitions, use an **import** statement
 - Goes at the top of your program (after the first comments)
- **Benefits** of functions/definitions in modules
 - Don't need to rewrite someone else's code
 - If it's in a module, it is very efficient (in terms of computation speed and memory usage)

Jan 21, 2008


Sprenkle - CS111

assign_constant.py

2

Programming Building Blocks

- Each type of statement is a building block
 - Initialization/Assignment
 - Arithmetic, string concatenation, functions
 - Print
 - Import
- We can combine them to create more complex programs
 - Solutions to problems



Jan 21, 2008

Sprenkle - CS111

3

Design Patterns

- General, repeatable solution to a commonly occurring problem in software design
 - Template for solution


Jan 21, 2008

Sprenkle - CS111

4

Design Patterns

- General, repeatable solution to a commonly occurring problem in software design
 - Template for solution
- Example (**Standard Algorithm**)
 - Get input from user
 - Do some computation
 - Display output
- **Today:** learn new building block, new design pattern




Jan 21, 2008

Sprenkle - CS111

5

Looping/Repetition




Jan 21, 2008

Sprenkle - CS111

6

The **for** Loop

- Use when know how many times loop will execute
 - Repeat N times



Jan 21, 2008

Sprengle - CS111

7

Using the **for** Loop

- Use when know how many times loop will execute
 - Repeat N times

```
for i in xrange(10):
    statement_1
    statement_2
    ...
    statement_n
```

Annotations:

- Times to repeat:** Points to `xrange(10)`.
- "Body" of for loop:** Points to the statements inside the loop.
- Gets repeated:** Points to the statements inside the loop.
- Note indentation:** Points to the statements inside the loop.

Jan 21, 2008

Sprengle - CS111

8

Using the **for** Loop

- If only **one** statement to repeat

```
for i in xrange(5): print "Hello!"
```

Jan 21, 2008


Sprengle - CS111

simple_for.py

9

What Goes in the Loop Body?

- Make PB&J Sandwich
 - Gather materials (bread, PB, J, knives, plate)
 - Open bread
 - Put 2 pieces of bread on plate
 - Spread PB on one side of one slice
 - Spread Jelly on one side of one slice
 - Place PB-side facedown on Jelly-side of bread
 - Close bread
 - Clean knife
 - Put away materials



Jan 21, 2008

Sprengle - CS111

10

What Goes in the Loop Body?

- Make PB&J Sandwich

Loop Body	➤ Gather materials (bread, PB, J, knives, plate)	Initialization
	➤ Open bread	
	➤ Put 2 pieces of bread on plate	Finalization
	➤ Spread PB on one side of one slice	
	➤ Spread Jelly on one side of one slice	
	➤ Place PB-side facedown on Jelly-side of bread	
	➤ Close bread	
	➤ Clean knife	
	➤ Put away materials	

Jan 21, 2008

Sprengle - CS111

11

Using the **for** Loop

- Good for when know how many times loop will execute
 - Repeat N times

```
for i in xrange(10):
    statement_1
    statement_2
    ...
    statement_n
```

Annotations:

- Times to repeat:** Points to `xrange(10)`.
- "Body" of for loop:** Points to the statements inside the loop.
- Gets repeated:** Points to the statements inside the loop.
- Note indentation:** Points to the statements inside the loop.

Jan 21, 2008

Sprengle - CS111

12

Analyzing xrange ()

- **xrange** is a built-in function
- What does **xrange** do, exactly?
 - Simulate on paper

Jan 21, 2008

Sprenkle - CS111 xrange_analysis.py 13

xrange([start,] stop[, step])

- What does the above signature mean?

Jan 21, 2008

Sprenkle - CS111

14

xrange([start,] stop[, step])

- 1 argument: xrange(stop)
- 2 arguments: xrange(start, stop)
- 3 arguments: xrange(start, stop, step)

Jan 21, 2008

Sprenkle - CS111 using_xrange.py 15

xrange([start,] stop[, step])


- 1 argument: xrange(stop)
 - Defaults: start = 0, step = 1
 - Iterates from 0 to stop-1 with step size=1
- 2 arguments: xrange(start, stop)
 - Default: step = 1
 - Iterates from start to stop-1 with step size=1
- 3 arguments: xrange(start, stop, step)
 - Iterates from start to stop-1 with step size=step

Jan 21, 2008

Sprenkle - CS111 using_xrange.py 16

xrange ()

- **xrange** is a built-in function
 - 1 argument: xrange(stop)
 - 2 arguments: xrange(start, stop)
 - 3 arguments: xrange(start, stop, step)



xrange(10)
xrange(0,10)

[start, stop)


Jan 21, 2008

Sprenkle - CS111


17

xrange ()

xrange(1, 15, 3):



xrange(5, -15, -5):



Jan 21, 2008


Sprenkle - CS111

new_for.py 18


Practice

Place these: ● ○
Which direction?


xrange(2, 14, 2):



xrange(8, -10, -3):



xrange(-5, 15, -3):




Jan 21, 2008

Sprengle - CS111


19

Practice Solution


xrange(2, 14, 2):



xrange(8, -10, -3):



xrange(-5, 15, -3):



Jan 21, 2008

Sprengle - CS111

20

Programming Practice

- Add 5 numbers, inputted by the user
 - After implementing, simulate running on computer

Jan 21, 2008

Sprengle - CS111

sum5.py

21

Accumulator Design Pattern

- Initialize accumulator variable
- Loop until done
 - Update the value of the accumulator
- Display result

Jan 21, 2008

Sprengle - CS111

22

Programming Practice

- Average 5 numbers inputted by the user

Jan 21, 2008

Sprengle - CS111

average5.py

23

This Week

- Tuesday: Lab 2
 - Lab still due on Friday
- Wednesday: Advanced for Loop
- Friday: no class
 - Mock Convention

Jan 21, 2008

Sprengle - CS111

24