

## Objectives

- More on Functions
  - Scope, variable lifetime

March 3, 2010

Sprenkle - CSCI111

1

## Lab Review

- Combinations of building block
- Faster recognition of how to solve
  - String without spaces → accumulate string!
- Iterative problem solving

March 3, 2010

Sprenkle - CSCI111

2

## Review: Functions

- What is the keyword to create a new function?
- What is the keyword to give output from a function?
- How do we give input to a function?
- Why write functions?

March 3, 2010

Sprenkle - CSCI111

3

## Review: Functions

- In general, a function can have
  - 0 or more inputs (the parameters)
  - 0 or 1 outputs (what is returned)
- When we define a function, we know its inputs and if it has output




March 3, 2010

Sprenkle - CSCI111

4

## Review: Syntax of Function Definition



March 3, 2010

Sprenkle - CSCI111

5

## Review: Parameters

- **Formal Parameters** are the variables named in the function definition
- **Actual Parameters** or **Arguments** are variables or literals that really get used when the function is called.

Defined: **def** round(x, n) :  
Use: roundCelc = round(celc, 2)

Formal & actual parameters must match in **order, number, and type!**

March 3, 2010

Sprenkle - CSCI111

6

## Review: Function Output

- When the code reaches a statement like  
`return x`  
the function stops executing and  
`x` is the **output returned** to the place where  
function was called
- For functions that don't have explicit output,  
`return` does not have a value with it, e.g.,
  - `return`
  - Optional: don't need to have `return`

March 3, 2010

Sprenkle - CSCI111

7

## Function Input and Output

- What is the input and output to this function?

```
def metersToMiles(meters) :  
    METERS_TO_MILES = .0006215  
    miles = meters * METERS_TO_MILES  
    return miles
```

March 3, 2010

Sprenkle - CSCI111

8

## Function Input and Output

- 1 **input**: `meters`
- 1 **output**: the converted miles

```
def metersToMiles(meters) :  
    METERS_TO_MILES = .0006215  
    miles = meters * METERS_TO_MILES  
    return miles
```

March 3, 2010

Sprenkle - CSCI111

9

## Function Input and Output

- Identify input and output

```
def printVerse(animal, sound):  
    print BEGIN_END + EIEIO  
    print "And on that farm he had a " + animal + EIEIO  
    print "With a " + sound + ", " + sound + " here"  
    print "And a " + sound + ", " + sound + " there"  
    print "Here a", sound  
    print "There a", sound  
    print "Everywhere a " + sound + ", " + sound  
    print BEGIN_END + EIEIO  
    print
```

March 3, 2010

Sprenkle - CSCI111

10

## Function Input and Output

- 2 **inputs**: `animal` and `sound`
- 0 **outputs**
  - *Displays something but does not return anything*

```
def printVerse(animal, sound):  
    print BEGIN_END + EIEIO  
    print "And on that farm he had a " + animal + EIEIO  
    print "With a " + sound + ", " + sound + " here"  
    print "And a " + sound + ", " + sound + " there"  
    print "Here a", sound  
    print "There a", sound  
    print "Everywhere a " + sound + ", " + sound  
    print BEGIN_END + EIEIO  
    print
```

## Function Input and Output

- Input? Output?

```
def printMenu():  
    print "You have some options for what to do: "  
    print "Enter an 'F' to find a song"  
    print "Enter an 'S' to sort by Song title"  
    print "Enter an 'A' to sort by Album"  
    print "Enter an 'R' to sort by aRtist name"  
    print "Enter an 'H' to list your options again"  
    print "Enter a 'Q' to quit"
```

March 3, 2010

Sprenkle - CSCI111

12

## Function Input and Output

- 0 inputs and 0 outputs
  - Again, it *displays* something but does not **return** anything

```
def printMenu():
    print "You have some options for what to do: "
    print "Enter an 'F' to find a song"
    print "Enter an 'S' to sort by Song title"
    print "Enter an 'A' to sort by Album"
    print "Enter an 'R' to sort by aRtist name"
    print "Enter an 'H' to list your options again"
    print "Enter a 'Q' to quit"
```

March 3, 2010

Sprenkle - CSCI111

13

## Typical Refactoring Process

1. Identify functionality that should be put into a function
  - What is the function's input?
  - What is the function's output?
2. Define/write the function
  - Write descriptive comments
3. Call the function where appropriate
4. Create a main function that contains the "driver" for your program
  - Put at top of program
5. Call main at bottom of program

March 3, 2010

Sprenkle - CSCI111

14

## Converting functionality into functions

- binaryToDecimal.py
  - Converting from binary to decimal
  - *Checking if a string contains only binary numbers*
- Write comments for the functions

March 3, 2010

Sprenkle - CSCI111

15

## Review: Why write functions?

- Allows you to break up a hard problem into smaller, more manageable parts
- Makes your code easier to understand
- Hides implementation details (*abstraction*)
  - Provides interface (input, output)
- Makes part of the code reusable so that you:
  - Only have to write function code once
  - Can debug it all at once
    - Isolates errors
  - Can make changes in one function (maintainability)

Similar to benefits of OO Programming

March 3, 2010

Sprenkle - CSCI111

16

## VARIABLE LIFETIMES AND SCOPE

March 3, 2010

Sprenkle - CSCI111

17

## What does this program output?

```
def main():
    x = 10
    sum = sumEvens( x )
    print "The sum of even #s up to", x, "is", sum

def sumEvens(limit):
    total = 0
    for x in xrange(0, limit, 2):
        total += x
    return total

main()
```

March 3, 2010

Sprenkle - CSCI111

18

## Function Variables

```
def main():
    x = 10
    sum = sumEvens( x )
    print "The sum of even #s up to", x, "is", sum

def sumEvens(limit):
    total = 0
    for x in xrange(0, limit, 2):
        total += x
    return total

main()
```

Why can we name two variables x?

March 3, 2010

Sprenkle - CSCI111

mystery.py

19

## Tracing through Execution

```
def main():
    x = 10
    sum = sumEvens( x )
    print "The sum of even #s up to", x, "is", sum

def sumEvens(limit):
    total = 0
    for x in xrange(0, limit, 2):
        total += x
    return total

main()
```

When you call main(), that means you want me to execute this function

Defines functions

March 3, 2010

Sprenkle - CSCI111

20

## Function Variables

```
def main() :
    x=10
    sum = sumEvens( x )
    print "The sum of even #s up to", x, "is", sum

def sumEvens(limit) :
    total = 0
    for x in xrange(0, limit, 2):
        total += x
    return total

main()
```

Function names are like last names

The stack

Variable names are like first names

main	x	10
------	---	----

March 3, 2010

Sprenkle - CSCI111

21

## Function Variables

```
def main() :
    x=10
    sum = sumEvens( x )
    print "The sum of even #s up to", x, "is", sum

def sumEvens(limit) :
    total = 0
    for x in xrange(0, limit, 2):
        total += x
    return total

main()
```

Called the function sumEvens Add its parameters to the stack

sum	limit	10
Evens	total	0
main	x	10

March 3, 2010

Sprenkle - CSCI111

22

## Function Variables

```
def main() :
    x=10
    sum = sumEvens( x )
    print "The sum of even #s up to", x, "is", sum

def sumEvens(limit) :
    total = 0
    for x in xrange(0, limit, 2):
        total += x
    return total

main()
```

sum	limit	10
Evens	total	0
main	x	10

March 3, 2010

Sprenkle - CSCI111

23

## Function Variables

```
def main() :
    x=10
    sum = sumEvens( x )
    print "The sum of even #s up to", x, "is", sum

def sumEvens(limit) :
    total = 0
    for x in xrange(0, limit, 2):
        total += x
    return total

main()
```

sum	limit	10
Evens	total	0
main	x	10

March 3, 2010

Sprenkle - CSCI111

24

## Function Variables

```
def main() :
    x=10
    sum = sumEvens( x )
    print "The sum of even #s up to", x, "is", sum

def sumEvens(limit) :
    total = 0
    for x in xrange(0, limit, 2):
        total += x
    return total

main()
```

sum	limit	10
Evens	total	20
	x	8
main	x	10

March 3, 2010

Sprenkle - CSCI111

25

## Function Variables

```
def main() :
    x=10
    sum = sumEvens( x )
    print "The sum of even #s up to", x, "is", sum

def sumEvens(limit) :
    total = 0
    for x in xrange(0, limit, 2):
        total += x
    return total

main()
```

Function `sumEvens` returned  
 • no longer have to keep track of its variables on stack  
 • lifetime of those variables is over

main	sum	20
	x	10

March 3, 2010

Sprenkle - CSCI111

26

## Function Variables

```
def main() :
    x=10
    sum = sumEvens( x )
    print "The sum of even #s up to", x, "is", sum

def sumEvens(limit) :
    total = 0
    for x in xrange(0, limit, 2):
        total += x
    return total

main()
```

main	x	10
	sum	20

March 3, 2010

Sprenkle - CSCI111

27

## Variable Scope

- Functions can have the same parameter and variable names as other functions
  - Need to look at the variable's **scope** to determine which one you're looking at
  - Use the stack to figure out which variable you're using
- Scope levels
  - Local scope** (also called **function scope**)
    - Can only be seen within the function
  - Global scope** (also called **file scope**)
    - Whole program can access
    - More on these later

March 3, 2010

Sprenkle - CSCI111

28

## Function Scope

- What variables can we "see" (i.e., use)?

```
def main():
    binary_string = raw_input("Enter a binary #: ")
    if not isBinary(binary_string):
        print "That is not a binary string"
        sys.exit()
    decVal = binaryToDecimal(binary_string)
    print "The decimal value is", decVal

def isBinary(string):
    for bit in string:
        if bit != "0" and bit != "1":
            return False
    return True
```

March 3, 2010

Sprenkle - CSCI111

29

## Variable Scope

- Practice: `scope.py`
  - Trace through program--what does it do?
- Answer questions in program...

March 3, 2010

Sprenkle - CSCI111

30

## Practice

- What is the output of this program?

➤ Example: user enters 4

```
def main():
    num = input("Enter a number to be squared: ")
    square = square(num)
    print "The square is:", square

def square(n):
    return n * n

main()
```

March 3, 2010

Sprenkle - CSCI111

practice1.py

31

## Practice

- What is the output of this program?

➤ Example: user enters 4

```
def main():
    num = input("Enter a number to be squared: ")
    squared = square(num)
    print "The square is:", squared
    print "The original num was:", n

def square(n):
    return n * n

main()
```

March 3, 2010

Sprenkle - CSCI111

practice2.py

32

## Practice

- What is the output of this program?

➤ Example: user enters 4

```
def main():
    num = input("Enter a number to be squared: ")
    squared = square(num)
    print "The square is:", squared
    print "The original num was:", n

def square(n):
    return n * n

main()
```

Error! **n** does not  
have a value in  
function **main()**

March 3, 2010

Sprenkle - CSCI111

33

## Variable Scope

- Know "lifetime" of variable
  - Only during execution of function
  - Related to idea of "scope"
- What about variables outside of functions?
  - Example: `non_function_vars.py`

March 3, 2010

Sprenkle - CSCI111

34

## Why We Don't Want Variables to Have Global Scope

- Other functions modify our data
  - Unintentionally from our point of view ...

March 3, 2010

Sprenkle - CSCI111

35

## Passing Parameters

- Only **copies** of the actual parameters are given to the function
  - For **immutable** data types (which are what we've talked about so far)
- The **actual** parameters in the calling code do not change
- Swap example:**
  - Swap two values in script
  - Then, put into a function

x = 5	→	x = 7
y = 7		y = 5

March 3, 2010

Sprenkle - CSCI111

36

## WHAT MAKES A GOOD FUNCTION?

March 3, 2010

Sprenkle - CSCI111

37

## Writing a “good” function

- Should be an “intuitive chunk”
  - Doesn’t do too much or too little
- Should be reusable
- Always have comment that tells what the function does

March 3, 2010

Sprenkle - CSCI111

38

## Good vs. Bad Functions

- Bad: Does too little

```
def getUserInput():  
    input = input("Enter a number")  
    return input
```

- Good: Validates the input

```
def getUserInput():  
    input = input("Enter a number")  
    while input <= 0:  
        print "Number must be positive"  
        input = input("Enter a number")  
    return input
```

March 3, 2010

Sprenkle - CSCI111

39

## Debugging Advice

- Build up your program in steps
  - Always write only small pieces of code
  - Test, debug. **Repeat**
- Write function body as part of **main**, test
  - Then, separate out into its own function
  - Similar to process using in lab probs
- Test function separately from other code
  - Comment out irrelevant code to make sure that the function behaves as expected

March 3, 2010

Sprenkle - CSCI111

40

## This Week

- Lab 6 due Friday
- Broader Issue: Volunteer Computing
- Reminder: Next Friday, Mar 12, Exam

March 3, 2010

Sprenkle - CSCI111

41