

Objectives

- Indefinite Loops
- Exam review

Jan 28, 2009

Sprenkle - CS111

1

Lab Review

- 1 “Challenge” problem
- 1 Application problem

Jan 28, 2009

Sprenkle - CS111

2

Indefinite Loops

- **for** loops are *definite* loops
 - Execute a *fixed* number of times
- Indefinite loops: keeps iterating until certain conditions are met
 - Depending on condition, no guarantee in advance of how many times the loop body will be executed

Jan 28, 2009

Sprenkle - CS111

3

While Loop Syntax

```
while condition :  
    statement1  
    statement2  
    ...  
    statementn
```

keyword

body of while loop

- Like a looped **if** statement
 - Execute statements **only** when condition is true

Jan 28, 2009

Sprenkle - CS111


4

While Loop

```
i = 0  
while i < 10 :  
    print "i equals ", i  
    i+=1  
print "Done", i
```

Questions:

- How many times will "i" get printed out?
- How many times is the condition evaluated?
- What is the value of i after the loop?



Jan 28, 2009

Sprenkle - CS111

while.py

5


While Loop

```
i = 0  
while i < 10 :  
    print "i equals ", i  
    i+=1  
print "Done", i
```

Initialize i before using in condition

Questions:

- How many times will "i" get printed out?
- How many times is the condition evaluated?
- What is the value of i after the loop?



Jan 28, 2009

Sprenkle - CS111

while.py

6

While vs. For Loops

- Any **for** loop can be translated into a **while** loop
 - **Not vice versa**
- while** loops are more **powerful** than **for** loops

Jan 28, 2009


Sprenkle - CS111

7

Convert to a **for** loop

We can convert this while loop into a for loop because it executes a **fixed** number of times.

```
i = 0
while i < 10 :
    print "i equals ", i
    i+=1
print "Done", i
```



Jan 28, 2009

Sprenkle - CS111

8

Comparing while and for

- What are the main differences between these loops?
- What are the advantages and disadvantages of each?

```
i = 0
while i < 10 :
    print "i equals ", i
    i+=1
print "Done", i
```

```
for i in xrange(10):
    print "i equals", i
print "Done", i
```

Jan 28, 2009

Sprenkle - CS111 [whilevsfor.py](#)

9

What Will This Loop Do?

```
count = 1
while count > 0:
    print count
    count += 1
```

Jan 28, 2009

Sprenkle - CS111

[loop.py](#)

10

Infinite Loop

- Condition will never be False so keeps executing

```
count = 1
while count > 0:
    print count
    count += 1
```
- To stop an executing program in Linux use
 - **Control-C**

Jan 28, 2009

Sprenkle - CS111

11

Infinite Loop Questions

- Is there ever a time that an infinite loop is wanted?
 - **Yes!** For example in web servers, we have something like

```
while True:
    listenForRequest()
    handleRequest()
```
- Can a computer automatically detect infinite loops?
 - No that is an **undecidable** problem
 - Best to **prevent** infinite loops (more later)
 - Benefit of Python's **for** loops: definite loops

Jan 28, 2009

Sprenkle - CS111

12

Unknown Number of Iterations

- Sums numbers input by user
 - Stop when the user inputs some designated stop value (**enter** key --> "")

Jan 28, 2009

Sprenkle - CS111

sumtillzero.py

13

Design Pattern: Sentinel Loop

- Sentinel: when to stop
 - "guard" to the loop

```
value = get input
while value != sentinel :
    process value
    value = get input
```

Jan 28, 2009

Sprenkle - CS111

14

Question

- How can we make sure that the loop actually stops (is not infinite)?

Jan 28, 2009

Sprenkle - CS111

15

Question

- How can we make sure that the loop actually stops (is not infinite)?
 - Update the condition's variable inside loop
 - Test
- How you'll usually detect an infinite loop...
 - "Why isn't my program giving me any output?"
 - If the program also isn't exiting, probably an infinite loop


Jan 28, 2009

Sprenkle - CS111

16

Use of break statement

- break** statement can "break you" out of a loop



Jan 28, 2009

17

while Loops: comparing use of break

```
# condition shows when loop # have to look inside loop to
# will stop executing # know when it stops
x= input("Enter a number: ")
while x % 2 != 0 :
    x = input("Try again.
    Enter a number: ")
print x, " is an even
    number."
```

Using break statements:
Best when loop has to
execute at least once.

Jan 28, 2009

Sprenkle - CS111

18

While vs. For Loops

- Any **for** loop can be translated into a **while** loop
 - Not vice versa
- while** loops are more **powerful** than **for** loops
 - Give an example of a **while** loop that can't be converted to a **for**

Jan 28, 2009

Sprenkle - CS111

19

Summary of Control-Flow Building Blocks (so far)

- Conditional statements
 - if, if-else, if-elif-else
- Loops
 - while, for

Jan 28, 2009

Sprenkle - CS111

20

Review: String Formatting

- What does this do?

```
print "%.2f deg F is %.2f deg C" % (degreesF, degreesC)
```

Jan 28, 2009

Sprenkle - CS111

21

Review: String Formatting

- Equivalent Statements

```
print "%.2f deg F is %.2f deg C" % (degreesF, degreesC)
```

```
print "%.2f" % degreesF, "deg F is %.2f deg C" % degreesC
```

```
print "%.2f" % degreesF, "deg F is", "%.2f" % degreesC, "deg C"
```

Jan 28, 2009

Sprenkle - CS111

22

Midterm Prep

- Cumulative up to today
 - We keep using the ideas from the first day of class
 - Basic Linux commands used during every lab
- Similar problems as in handouts, class discussion, labs
- Read code and explain what it does
 - What it displays as output
- Sections: Very Short Answer, Short Answer, Write Code
- Online prep document

Jan 28, 2009

Sprenkle - CS111

23

Grading Overview

- Labs: 38%
- 2 Exams: 29%
- Final: 20%
- Broader Issues: 8%
- Participation: 5%

Jan 28, 2009

Sprenkle - CS111

24