

Objectives

- Improving program readability
- Introduction to Object-Oriented Programming
- Introduction to APIs
- Problem-solving using APIs

Jan 23, 2012

Sprenkle - CSCI111

1

Review

- What are benefits of functions?
- How do we call functions?
- What do we get access to functions that are in a module?
 - How does using the imported functions change with each type of import statement?

Jan 23, 2012

Sprenkle - CSCI111

2

Benefits of Functions

- Reuse, simplify code
- Functions written by others
 - Well-written, efficiency
 - Abstraction: it works, that's all that matters!
- Greatly increase code you can write by leveraging others' code

Jan 23, 2012

Sprenkle - CSCI111

3

Review: VA Lottery: Pick 4

- To play: you pick 4 numbers between 0 and 9
- To win: select the numbers that are selected by the magic ping-pong ball machine
- Your job: Simulate the magic ping-pong ball machines

Jan 23, 2012

Sprenkle - CSCI111

`pick4.py`

4

VA Lottery: Mega Millions

- To play: you pick 5 numbers between 1 and 56
 - Ignoring rule: 1 Mega Ball number between 1 and 46
- Your job: Simulate the result of the magic ping-pong ball machines
 - How difficult to modify the last program?
 - What could we do to make easier?

Jan 23, 2012

Sprenkle - CSCI111 `megamillions.py`

5

Constants

- Special variables whose values are defined once and never changed
 - By convention, not enforced by interpreter
- By convention
 - A constant's name is all caps
 - Typically defined at top of program → easy to find, change
- Examples:

```
NUM_CHOICES = 4
MIN_VALUE = 0
```

Never assigned values in remainder of program

Jan 23, 2012

Sprenkle - CSCI111

6

Improving Code Readability

- Comments
 - Describe blocks of code at a high level
- Output/Display
 - Descriptive, explains what program outputs
- Constants
 - Change one value (at top of program) to change value everywhere in program
 - Flexible programs
 - Gets rid of “magic numbers”
 - Give a clear name and purpose to values

Jan 23, 2012

Sprenkle - CSCI111

7

Improving Code Readability/Usability

- What does this program do?
 - How would you figure it out?
- What would you do to improve the program's readability and usability?

program_before.py
program_after.py

Jan 23, 2012

Sprenkle - CSCI111

8

Programming Paradigm: Imperative

- Most modern programming languages are **imperative**
- Have **data** (numbers and strings in variables)
- Perform **operations** on data using operations, such as + (addition and concatenation)
- Data and operations are separate
- Add to imperative:
object-oriented programming

Jan 23, 2012

Sprenkle - CSCI111

9

Super Power: Psychokinesis

OBJECT-ORIENTED PROGRAMMING

Jan 23, 2012

Sprenkle - CSCI111

10

Object-Oriented Programming

- Program is a collection of **objects**
- Objects **combine** data and methods together
- Objects interact by invoking **methods** on other objects
 - Methods perform some operation on object

Jan 23, 2012

Sprenkle - CSCI111

11

Object-Oriented Programming

- Program is a collection of **objects**
- Objects **combine** data and methods together
- Objects interact by invoking **methods** on other objects
 - Methods perform some operation on object




Jan 23, 2012

Sprenkle - CSCI111

12

Object-Oriented Programming

- We've been using objects
 - Just didn't call them objects
- For example: **str** is a data type (or **class**)
 - We created objects of type (class) **string**
 - `animal = "cow"`
 - `courseName = "csci111"`



Jan 23, 2012

Sprenkle - CSCI111

13

Example of OO Programming Abstraction

- Think of a TV – It's an **object**
- What can you do to your TV using one of two **interfaces**: the remote or the buttons on the TV?

Jan 23, 2012

Sprenkle - CSCI111

14

Example of OO Programming Abstraction

- Think of a TV – it's an **object**
- What can you do to your TV using one of two **interfaces**: the remote or the buttons on the TV?
 - Turn on/off
 - Change channel
 - Change volume
 - ...
- You don't know **how** that operation is being done (i.e., implemented)
 - Just know **what it does** and that it **works**

methods

Jan 23, 2012

Sprenkle - CSCI111

15

Example of OO Programming Abstraction

- Your TV is an **object**
- **Methods** you can call on your TV:
 - Turn on/off
 - Change channel
 - Change volume
 - ...
- TV is a **class**, a.k.a., a data **type**
 - Your TV (identified by myTV) is an object of type TV
 - You can call the above methods on any object of type TV

Jan 23, 2012

Sprenkle - CSCI111

16

Object-Oriented Programming

- Objects combine **data** and **methods** together
 - Provides **interface** (methods) that users interact with



Use an **Application Programming Interface (API)** to interact with a set of classes.

Jan 23, 2012

Sprenkle - CSCI111

17

Class Libraries

- Python provides libraries of classes
 - Defines methods that you can call on objects from those classes
 - **str** class provides a bunch of useful methods
 - More on that later
- Third-party libraries
 - Written by non-Python people
 - Can write programs using these libraries too

Jan 23, 2012

Sprenkle - CSCI111

18

Benefits of Object-Oriented Programming

- **Abstraction**
 - Hides details of underlying implementation
 - Easier to change implementation
- Easy reuse of code
- Collects related data/methods together
 - Easier to reason about data
- Less code in main program

Jan 23, 2012

Sprenkle - CSCI111

19

Using a Graphics Module/Library

- Allows us to handle graphical input and output
 - Example output: Pictures
 - Example input: Mouse clicks
 - Defines a collection of related graphics **classes**
 - Not part of a standard Python distribution
 - Need to import from `graphics.py`
- ➡ Use the library to help us learn OO programming

Jan 23, 2012

Sprenkle - CSCI111

20

USING A GRAPHICS MODULE

Jan 23, 2012

Sprenkle - CSCI111

21

Using a Graphics Module/Library


- Handout lists the various classes
 - **Constructor** is in bold
 - Creates an object of that type
 - For each class, lists *some* of their methods and parameters
 - Drawn objects have some common methods
 - Listed at end of handout
- Known as an **API**
 - **Application Programming Interface**

Jan 23, 2012

Sprenkle - CSCI111

22

Example of Output



Jan 23, 2012

Sprenkle - CSCI111

23

Using the API: Constructors

- To create an object of a certain type/class, use the **constructor** for that type/class
 - Syntax:

```
objName = ClassName([parameters])
```
 - Note:
 - Class names typically begin with capital letter
 - Object names begin with lowercase letter
 - **objname** is known as an **instance** of the class
- Example: To create a `GraphWin` object that's identified by window

```
window = GraphWin("My Window",200,200)
```

Jan 23, 2012

Sprenkle - CSCI111

24

Using the API: Methods

- To call a **method** on an object,
 - Syntax:


```
objName.methodName([parameters])
```
 - Method names typically begin with lowercase letter
 - Similar to calling *functions*
- Example: To change the background color of a GraphWin object named window

```
window.setBackground("blue")
```

Jan 23, 2012

Sprenkle - CSCI111

25

Using the API: Methods

- A method sometimes **returns output**, which you may want to save in a variable
 - Class's API should say if method returns output
- Example: if you want to know the width of a GraphWin object named window

```
width = window.getWidth()
```

Jan 23, 2012

Sprenkle - CSCI111

26

What Does This Code Do?

- Use OO terminology previously defined

```
from graphics import *
win = GraphWin("My Circle", 100, 100)
point = Point(50,50)
c = Circle(point, 10)
c.draw(win)
win.getMouse()
```

Jan 23, 2012

Sprenkle - CSCI111

27

What Does This Code Do?

- Use OO terminology previously defined

```
from graphics import *
win = GraphWin("My Circle", 100, 100)
point = Point(50,50)
c = Circle(point, 10)
c.draw(win)
win.getMouse()
```

GraphWin object
Also known as an **instance of the GraphWin class**

Constructor

Method called on GraphWin object

Note: Class names start with capital letters, Method names start with lowercase letters

Jan 23, 2012

Using the Graphics Library


- In general, graphics are drawn on a canvas
 - A canvas is a 2-dimensional grid of pixels
- For our Graphics library, our canvas is a *window*
 - Specifically an **instance of the GraphWin class**
 - By default, a GraphWin object is 200x200 pixels

Jan 23, 2012

Sprenkle - CSCI111

29

A GraphWin Object's Canvas



Jan 23, 2012

Sprenkle - CSCI111

30

Reading Code

- After this program executes, what does the window look like?

```
from graphics import *

win = GraphWin("My Circle", 100, 100)
c = Circle(Point(50,50), 10)
c.draw(win)
win.getMouse()
```

graphics_test.py

Jan 23, 2012

Sprenkle - CSCI111

31

The GraphWin Class

- All parameters to the constructor are optional
- Could call constructor as

Call	Meaning
GraphWin()	Title, width, height to defaults ("Graphics Window", 200, 200)
GraphWin(<title>)	Width, height to defaults
GraphWin(<title>, <width>)	Height to default
GraphWin(<title>, <width>, <height>)	

Jan 23, 2012

Sprenkle - CSCI111

32

The GraphWin API

- Accessor** methods for GraphWin
 - Return some information about the GraphWin
- Example methods:
 - <GraphWinObj>.getWidth()
 - <GraphWinObj>.getHeight()

Jan 23, 2012

Sprenkle - CSCI111

33

The GraphWin API

- <GraphWinObj>.setBackground(<color>)
 - Colors are strings, such as "red" or "purple"
 - Can add numbers to end of string for darker colors, e.g., "red2", "red3", "red4"

```
win = GraphWin()
win.setBackground("purple")
```

- Does *not* return anything to shell
- Called for change in **win**'s state, i.e., this method is a **mutator**

Jan 23, 2012

Sprenkle - CSCI111

34

Colors

- Strings, such as "blue4"
- Can also create colors using the **function** color_rgb(<red>, <green>, <blue>)
 - Parameters in the range [0,255]
 - Example use:

```
darkBlueGreen = color_rgb(10, 100, 100)
win.setBackground(darkBlueGreen)
```

 - Background is a dark blue/green color
 - Example color codes:
 - http://en.wikipedia.org/wiki/List_of_colors

Jan 23, 2012

Sprenkle - CSCI111

35

General Categories of Methods

- Accessor**
 - Returns information about the object
 - Example: getWidth()
- Mutator**
 - Changes the state of the object
 - i.e., changes something about the object
 - Example: setBackground()

Jan 23, 2012

Sprenkle - CSCI111

36

Using the Graphics Library

- How do we create an instance of a Rectangle?
- Draw the rectangle?
- Shift the instance of the Rectangle class to the **right** 10 pixels
- What are the x- and y- coordinates of the upper-left corner of the Rectangle now?

Jan 23, 2012

Sprenkle - CSCI111 `rectangle.py`

37

OO Terminology Summary

Term	Definition	Examples
Class	A data type. Defines the data and operations for members of the class	string, TV, GraphWin
Object	An <i>instance</i> of a specific class	animal, myTV, window
Method	Operations you can call on an object	setBackground(<color>), getWidth()
Constructor	Special method to create an object of a certain type/class	GraphWin(), str(1234)

Jan 23, 2012

Sprenkle - CSCI111

38

Looking Ahead

- Broader Issue
 - Read 2 short articles for Friday
- Lab tomorrow
 - Practice for loops, functions, and OO programming
- Next Monday
 - 11:15 a.m. – Andy Danner's GIS/CS talk
 - 10 points extra credit for answering questions on Sakai

Jan 23, 2012

Sprenkle - CSCI111

39