

Objectives

Dynamic Programming

- Overview
- Fibonacci
- Weighted scheduling

Mar 18, 2009

CS211

1

Algorithmic Paradigms

Greedy. Build up a solution incrementally, myopically optimizing some local criterion

Divide-and-conquer. Break up a problem into sub-problems, solve each sub-problem independently, and combine solution to sub-problems to form solution to original problem

Dynamic programming. Break up a problem into a series of overlapping sub-problems, and build up solutions to larger and larger sub-problems

Mar 18, 2009

CS211

2

Dynamic Programming History

Richard Bellman pioneered systematic study of dynamic programming in 1950s

Etymology

- Dynamic programming = planning over time
 - Not our typical use of programming
- Secretary of Defense was hostile to mathematical research
- Bellman sought an impressive name to avoid confrontation
 - "it's impossible to use dynamic in a pejorative sense"
 - "something not even a Congressman could object to"

Mar 18, 2009

Reference: Bellman, R. E. *Eye of the Hurricane, An Autobiography.*

3

WARMUP: FIBONACCI SEQUENCE

Mar 18, 2009

CS211

4

How Would You Solve Fibonacci Sequence?

Input: the number of fibonacci numbers I want

Output: display the list of fibonacci numbers

Sequence:

- $F_0 = F_1 = 1$
- $F_n = F_{n-1} + F_{n-2}$

Mar 18, 2009

CS211

5

Soln 1: Using a List

Typical Solution:

```
fibs = []           # create an empty list
fibs.append(1)     # append the first two Fib numbers
fibs.append(1)
print 1, 1,
for x in xrange(2, N+1):
    newfib = fibs[x-1]+fibs[x-2]   Building up solution
    print newfib,
    fibs.append(newfib)
print fibs         # print out the list
```

Running time? Space cost?

Do we need a whole list?

Mar 18, 2009

CS211

6

Soln 2: Using Three Variables

Only need the solutions to the last two problems
($F[k-1]$, $F[k-2]$)

```
lastNum = 1
twoAgo = 1
print twoAgo, lastNum,

for n in xrange(2, N+1):

    nthNum = twoAgo + lastNum
    print nthNum,

    twoAgo = lastNum
    lastNum = nthNum
```

Write as a recurrence

Mar 18, 2009

CS211

7

Soln 3: Recursion

```
def fibonacci(n):
    return fibonacci(n-1) + fibonacci(n-2)
```

What is the running time of this algorithm?

Mar 18, 2009

CS211

8

Dynamic Programming Memoization Process

Create a table with the possible inputs

If the value is in the table, return it (without recomputing it); Otherwise, call function recursively

- Add value to table for future reference

Mar 18, 2009

CS211

9

Memoization Example: Fibonacci

```
memoized_fibonacci(n):
    for j = 1 to n:
        results[j] = -1 # -1 means undefined

    return memoized_fib_rekurs(results, n)

memoized_fib_rekurs(results, n):
    if results[n] != -1: # value is defined
        return results[n]
    if n == 1:
        val = 1
    elif n == 2:
        val = 1
    else:
        val = memoized_fib_rekurs(results, n-2)
        val = val + memoized_fib_rekurs(results, n-1)
    results[n] = val
    return val
```

Runtime?

Mar 18, 2009

CS211

10

Memoization Example: Fibonacci

```
memoized_fibonacci(n):
    for j = 1 to n:
        results[j] = -1 # -1 means undefined
    results[1] = 1
    results[2] = 1

    return memoized_fib_rekurs(results, n)

memoized_fib_rekurs(results, n):
    if results[n] != -1: # value is defined
        return results[n]

    val = memoized_fib_rekurs(results, n-2)
    val = val + memoized_fib_rekurs(results, n-1)
    results[n] = val
    return val
```

Mar 18, 2009


CS211

11

WEIGHTED INTERVAL SCHEDULING

Weighted Interval Scheduling

Job j starts at s_j , finishes at f_j , and has weight or value v_j
 Two jobs are **compatible** if they don't overlap
Goal: find maximum **weight** subset of mutually compatible jobs



Mar 18, 2009 CS211 13

Unweighted Interval Scheduling Review

Recall. Greedy algorithm works if all weights are 1.

- Consider jobs in ascending order of finish time
- Add job to subset if it is compatible with previously chosen jobs

What happens if we add weights to the problem?


Mar 18, 2009 CS211 14

Limitation of Greedy Algorithm

Recall. Greedy algorithm works if all weights are 1.

- Consider jobs in ascending order of finish time
- Add job to subset if it is compatible with previously chosen jobs

Observation. Greedy algorithm can fail spectacularly if arbitrary weights are allowed




Mar 18, 2009 CS211 15

Weighted Interval Scheduling

Notation. Label jobs by finishing time: $f_1 \leq f_2 \leq \dots \leq f_n$

Def. $p(j)$ = largest index $i < j$ such that job i is compatible with j

Ex: $p(8) = 5, p(7) = 3, p(2) = 0$



Mar 18, 2009 CS211 16

Dynamic Programming

Assume we have an optimal solution

Notation. $OPT(j)$ = value of optimal solution to the *problem* consisting of job requests $1, 2, \dots, j$

- What is something *obvious* we can say about the optimal solution with respect to job j ?

Mar 18, 2009 CS211 17

Dynamic Programming: Binary Choice

Notation. $OPT(j)$ = value of optimal solution to the *problem* consisting of job requests $1, 2, \dots, j$

- Case 1: OPT selects job j
- Case 2: OPT does not select job j

- Explore both of these cases...
 - What jobs are in OPT ? Which are not?
- Keep in mind our definition of p

Mar 18, 2009 CS211 18

Weighted Interval Scheduling

Notation. Label jobs by finishing time: $f_1 \leq f_2 \leq \dots \leq f_n$

Def. $p(j)$ = largest index $i < j$ such that job i is compatible with j

Ex: $p(8) = 5, p(7) = 3, p(2) = 0$

Mar 18, 2009 CS211 19

Dynamic Programming: Binary Choice

Notation. $OPT(j)$ = value of optimal solution to the *problem* consisting of job requests $1, 2, \dots, j$

- Case 1: OPT selects job j
 - can't use incompatible jobs $\{p(j) + 1, p(j) + 2, \dots, j - 1\}$
 - must include optimal solution to problem consisting of remaining compatible jobs $1, 2, \dots, p(j)$
- Case 2: OPT does not select job j
 - must include optimal solution to problem consisting of remaining compatible jobs $1, 2, \dots, j - 1$

optimal substructure

Formulate $OPT(j)$ as a recurrence relation

Mar 18, 2009 CS211 20

Dynamic Programming: Binary Choice

Notation. $OPT(j)$ = value of optimal solution to the *problem* consisting of job requests $1, 2, \dots, j$

- Case 1: OPT selects job j
 - can't use incompatible jobs $\{p(j) + 1, p(j) + 2, \dots, j - 1\}$
 - must include optimal solution to problem consisting of remaining compatible jobs $1, 2, \dots, p(j)$
- Case 2: OPT does not select job j
 - must include optimal solution to problem consisting of remaining compatible jobs $1, 2, \dots, j - 1$

Two options: $OPT(j) = v_j + OPT(p(j))$
 $OPT(j) = OPT(j-1)$

Formulate $OPT(j)$ in terms of smaller subproblems
Which should we choose?

Mar 18, 2009 CS211 21

Dynamic Programming: Binary Choice

Notation. OPT = value of optimal solution to the *problem* consisting of job requests $1, 2, \dots, j$

- Case 1: OPT selects job j
 - can't use incompatible jobs $\{p(j) + 1, p(j) + 2, \dots, j - 1\}$
 - must include optimal solution to problem consisting of remaining compatible jobs $1, 2, \dots, p(j)$
- Case 2: OPT does not select job j
 - must include optimal solution to problem consisting of remaining compatible jobs $1, 2, \dots, j - 1$

$OPT(j) = \begin{cases} 0 & \text{if } j = 0 \\ \max \{ v_j + OPT(p(j)), OPT(j-1) \} & \text{otherwise} \end{cases}$

Choose the better of the two solutions

Mar 18, 2009 CS211 22

Weighted Interval Scheduling: Recursive Algorithm

Input: n jobs (associated start time s_j , finish time f_j , and value v_j)

Sort jobs by finish times so that $f_1 \leq f_2 \leq \dots \leq f_n$

Compute $p(1), p(2), \dots, p(n)$

Compute- $OPT(j)$

```

if  $j = 0$ 
    return 0
else
    return  $\max(v_j + \text{Compute-}OPT(p(j)), \text{Compute-}OPT(j-1))$ 
    
```

What is the run time?
 (Trace for $n = 5$)

Mar 18, 2009 CS211 23

Weighted Interval Scheduling: Brute Force

Observation. Redundant sub-problems \Rightarrow exponential algorithms

Ex. Number of recursive calls for family of "layered" instances grows like Fibonacci sequence.

$p(1) = 0, p(j) = j - 2$

Mar 18, 2009 CS211 24

Weighted Interval Scheduling: Memoization

Memoization. Store results of each sub-problem in a cache; lookup as needed.

Input: n jobs (associated start time s_j , finish time f_j , and value v_j)

Sort jobs by finish times so that $f_1 \leq f_2 \leq \dots \leq f_n$
 Compute $p(1), p(2), \dots, p(n)$

for $j = 1$ to n
 $M[j] = \text{empty}$ ← global array
 $M[0] = 0$ ← Because we have jobs whose $p(j) = 0$

M-Compute-Opt(j):
 if $M[j]$ is empty:
 $M[j] = \max(v_j + \text{M-Compute-Opt}(p(j)), \text{M-Compute-Opt}(j-1))$
 return $M[j]$

Need to analyze runtime...


Mar 18, 2009

CS211

25

Example

Jobs labeled with name - weight/value




M	0	A	B	C	D	E	F	G	H

Mar 18, 2009

CS211

26

Example



M	0	A	B	C	D	E	F	G	H

Mar 18, 2009

CS211

27