

Objectives

Data structures: Heaps & Graphs

Jan 28, 2009

1

Review: Priority Queues

Can use priority queues to sort

Sort runtime should be $O(n \log n)$

However, cannot implement PQs with "known" data structures arrays and lists to meet desired runtime

→ Motivates use of Heap to implement PQ

→ **Goal:** show results in $O(n \log n)$ time

Jan 28, 2009

2

Implementing Priority Queues

Operation	Unsorted List	Sorted List	Sorted Array
StartHeap(N)			
Insert(H, v)			
FindMin(H)			
Delete(H, i)			
ExtractMin(H)			

Jan 28, 2009

3

Implementing Priority Queues

Operation	Unsorted List	Sorted List	Sorted Array
StartHeap(N)	$O(1)$	$O(1)$	$O(N)$
Insert(H, v)	$O(1)$	$O(n)$	$O(n)$
FindMin(H)	$O(n)$	$O(1)$	$O(1)$
Delete(H, i)	$O(n)$	$O(n)$	$O(n)$
ExtractMin(H)	$O(n)$	$O(1)$	$O(n)$


Jan 28, 2009

4

Review: Heap

Combines benefits of sorted array and list

Balanced binary tree




Jan 28, 2009

5

Implementing a Heap

Option 1: Use pointers

- Each node keeps
 - Element it stores, key
 - 3 pointers: 2 children, parent



Option 2: No pointers

- Requires knowing upper bound on n
- For node at position i
 - left child is at $2i$
 - right child is at $2i+1$



If know child's position, what is the position of parent?

Jan 28, 2009

6

Implementing a Heap: Operations

Adding an element?

- Could add element to last position
 - What are possible scenarios?
 - Heap is no longer balanced
 - Something that is almost a heap but a little off
 - Need a Heapify-up procedure to fix our heap

Jan 28, 2009

7

Heapify-Up

Heap Position where node added

```

Heapify-up(H, i):
  if i > 1 then
    let j=parent(i)=floor(i/2)
    if key[H[i]] < key[H[j]] then
      swap array entries H[i] and H[j]
      Heapify-up(H, j)
  
```

Can insert a new element in a heap of n elements in $O(\log n)$ time

Jan 28, 2009

8

Deleting an Element

Delete at position i

Not only removes an element

- Messes up heap order
- Leaves a "hole" in the heap


Not as straightforward as Heapify-Up

- Need to fill-in element where hole was
 - Patch hole: move n^{th} element into i^{th} spot
- Then adjust heap to be in order
 - At position i because moved n^{th} item up to i

Jan 28, 2009

9

Deleting an Element



Two possibilities: element w is


- Too small: violation is between it and parent → **Heapify-Up**
- Too big: with one or both children → **Heapify-Down**

Jan 28, 2009

10

Deleting an Element

Example where new key is too small



Delete 9


Replace with 5

Jan 28, 2009

11

Deleting an Element

Example where new key is too small



Delete 9

Replace with 5

But $5 < 6$, so need to **Heapify-Up**

Jan 28, 2009

12

Heapify-Down

```

Heapify-down(H, i):
  Let n = length(H)
  if 2i > n then
    Terminate with H unchanged
  else if 2i < n then
    let left=2i and right=2i+1
    let j be index that minimizes
      key[H[left]] and key[H[right]]
  else if 2i = n then
    Let j=2i


  if key[H[j]] < key[H[i]] then
    swap array entries H[i] and H[j]
    Heapify-down(H, j)

```

Jan 28, 2009

13


Practice: Heapify-Down



Jan 28, 2009

14


Practice: Heapify-Down



Jan 28, 2009

15

Practice: Heapify-Down



Jan 28, 2009

16

Runtime of Heapify-Down?

```

Heapify-down(H, i):
  Let n = length(H)
  if 2i > n then
    Terminate with H unchanged
  else if 2i < n then
    let left=2i and right=2i+1
    let j be index that minimizes
      key[H[left]] and key[H[right]]
  else if 2i = n then
    Let j=2i

  if key[H[j]] < key[H[i]] then
    swap array entries H[i] and H[j]
    Heapify-down(H, j)

```

Jan 28, 2009

17

Runtime of Heapify-Down: $O(\log n)$

Computation of j: $O(1)$

Swap: $O(1)$

How many swaps: $O(\log n)$

Jan 28, 2009

18

Implementing Priority Queues with Heaps

Operation	Description	Run Time
StartHeap(N)	Creates an empty heap that can hold N elements	
Insert(H, v)	Inserts item v into heap H	
FindMin(H)	Identifies minimum element in heap H but does not remove it	
Delete(H, i)	Deletes element in heap position i	
ExtractMin(H)	Identifies and deletes an element with minimum key from heap	

Jan 28, 2009

19

Implementing Priority Queues with Heaps

Operation	Description	Run Time
StartHeap(N)	Creates an empty heap that can hold N elements	$O(N)$
Insert(H, v)	Inserts item v into heap H	$O(\log n)$
FindMin(H)	Identifies minimum element in heap H but does not remove it	$O(1)$
Delete(H, i)	Deletes element in heap position i	$O(\log n)$
ExtractMin(H)	Identifies and deletes an element with minimum key from heap	$O(\log n)$

Jan 28, 2009

20

Implementing Priority Queues

Operation	Heap	Unsorted List	Sorted List
StartHeap(N)	$O(N)$		
Insert(H, v)	$O(\log n)$		
FindMin(H)	$O(1)$		
Delete(H, i)	$O(\log n)$		
ExtractMin(H)	$O(\log n)$		

Jan 28, 2009

21

Implementing Priority Queues

Operation	Heap	Unsorted List	Sorted List
StartHeap(N)	$O(N)$	$O(1)$	$O(1)$
Insert(H, v)	$O(\log n)$	$O(1)$	$O(n)$
FindMin(H)	$O(1)$	$O(n)$	$O(1)$
Delete(H, i)	$O(\log n)$	$O(n)$	$O(n)$
ExtractMin(H)	$O(\log n)$	$O(n)$	$O(1)$

Jan 28, 2009

22

Additional Heap Operations

Access given element of PQ

- Maintain additional array **Position** that stores current position of each element in heap

Operations:

- Delete(H, Position[v])
 - Does not increase overall running time
- ChangeKey(H, v, a)
 - Changes key value of element v to $\text{key}(v) = a$
 - Identify position of element v in array (Position array)
 - Change key, heapify

Jan 28, 2009

23

GRAPHS

Jan 28, 2009

24


Undirected Graphs $G = (V, E)$

V = nodes (vertices)

E = edges between pairs of nodes

Captures pairwise relationship between objects

Graph size parameters: $n = |V|$, $m = |E|$




$V = \{1, 2, 3, 4, 5, 6, 7, 8\}$
 $E = \{1-2, 1-3, 2-3, 2-4, 2-5, 3-5, 3-7, 3-8, 4-5, 5-6\}$
 $n = 8$
 $m = 11$

25

World Wide Web

Web graph

- Node: web page
- Edge: hyperlink from one page to another



Directed Graph

26

Social Networks


Node: people; Edge: relationship between 2 people

Everything Bad Is Good for You: How Today's Popular Culture Is Actually Making Us Smarter

- Television shows have complex plots, complex social networks

Social network of 24's Jack Bauer

Color Chart
 Nodes 0 edges Away Nodes 1 edges Away
 Nodes 2 edges Away Nodes 3 edges Away
 Unreachable Nodes in Black




<http://www.cs.duke.edu/csed/haranbeenet/modules.html>

29

Ecological Food Web

Food web graph

- Node = species
- Edge = from prey to predator



Directed Graph

Reference: <http://www.twingroves.district196.k12.il.us/Wetlands/Salamander/SalGraphics/salfoodweb.gif>

28

Graph Applications


Graph	Nodes	Edges
transportation	street intersections	highways
communication	computers	fiber optic cables
World Wide Web	web pages	hyperlinks
social	people	relationships
food web	species	predator-prey
software systems	functions	function calls
scheduling	tasks	precedence constraints
circuits	gates	wires

29

Graph Representation: Adjacency Matrix

$n \times n$ matrix with $A_{uv} = 1$ if (u, v) is an edge

- Two representations of each edge (symmetric matrix)
- Space?
- Checking if (u, v) is an edge?
- Identifying all edges?




	1	2	3	4	5	6	7	8
1	0	1	1	0	0	0	0	0
2	1	0	1	1	0	0	0	0
3	1	1	0	0	1	0	1	1
4	0	1	0	1	1	0	0	0
5	0	1	1	1	0	1	0	0
6	0	0	0	0	1	0	0	0
7	0	0	1	0	0	0	1	0
8	0	0	1	0	0	0	1	0

30

Graph Representation: Adjacency Matrix

$n \times n$ matrix with $A_{uv} = 1$ if (u, v) is an edge

- Two representations of each edge (symmetric matrix)
- Space proportional to n^2
- Checking if (u, v) is an edge takes $\Theta(1)$ time
- Identifying all edges takes $\Theta(n^2)$ time





	1	2	3	4	5	6	7	8
1	0	1	1	0	0	0	0	0
2	1	0	1	1	1	0	0	0
3	1	1	0	0	1	0	1	1
4	0	1	0	1	1	0	0	0
5	0	1	1	1	0	1	0	0
6	0	0	0	0	1	0	0	0
7	0	0	1	0	0	0	1	1
8	0	0	1	0	0	0	1	0

31

Graph Representation: Adjacency List

Node indexed array of lists

- Two representations of each edge
- Space?
- Checking if (u, v) is an edge?
- Identifying all edges?





32

Graph Representation: Adjacency List

Node indexed array of lists

- Two representations of each edge
- Space = $2m + n = O(m + n)$
- Checking if (u, v) is an edge takes $O(\deg(u))$ time
- Identifying all edges takes $\Theta(m + n)$ time



33


Paths and Connectivity

Def. A *path* in an undirected graph $G = (V, E)$ is a sequence P of nodes $v_1, v_2, \dots, v_{k-1}, v_k$

- each consecutive pair v_i, v_{i+1} is joined by an edge in E

Def. A path is *simple* if all nodes are distinct

Def. An undirected graph is *connected* if \forall pair of nodes u and v , there is a path between u and v




• Short path
• Distance

34

Cycles

Def. A *cycle* is a path $v_1, v_2, \dots, v_{k-1}, v_k$ in which $v_1 = v_k$, $k > 2$, and the first $k-1$ nodes are all distinct



cycle $C = 1-2-4-5-3-1$


35

Trees

Def. An undirected graph is a *tree* if it is connected and does not contain a cycle

Simplest connected graph

- Deleting any edge from a tree will disconnect it



36


Connectivity

s-t connectivity problem. Given two node s and t , is there a path between s and t ?

s-t shortest path problem. Given two node s and t , what is the length of the shortest path between s and t ?

Applications

- Facebook
- Maze traversal
- Kevin Bacon number
- Fewest number of hops in a communication network




43

Breadth First Search

Intuition. Explore outward from s in all possible directions, adding nodes one "layer" at a time

Algorithm

- $L_0 = \{s\}$
- L_1 = all neighbors of L_0
- L_2 = all nodes that do not belong to L_0 or L_1 , and that have an edge to a node in L_1
- L_{i+1} = all nodes that do not belong to an earlier layer, and that have an edge to a node in L_i




Theorem. For each i , L_i consists of all nodes at distance exactly i from s . There is a path from s to t iff t appears in some layer.

44


Breadth First Search

Property. Let T be a BFS tree of $G = (V, E)$, and let (x, y) be an edge of G . Then the level of x and y differ by at most 1.


G :



(a)



(b)



(c)

45

Breadth First Search: Analysis

Theorem. The BFS implementation runs in $O(m + n)$ time if graph is given by its adjacency representation

Pf.

- Easy to prove $O(n^2)$ running time:
 - at most n lists $L[i]$
 - each node occurs on at most one list; for loop runs $\leq n$ times
 - when we consider node u , there are $\leq n$ incident edges (u, v) , and we spend $O(1)$ processing each edge

46

Breadth First Search: Analysis

Theorem. The BFS implementation runs in $O(m + n)$ time if graph is given by its adjacency representation

Pf.

- Actually runs in $O(m + n)$ time:
 - when we consider node u , there are $\deg(u)$ incident edges (u, v)
 - total time processing edges is $\sum_{u \in V} \deg(u) = 2m$

each edge (u, v) is counted exactly twice in sum: once in $\deg(u)$ and once in $\deg(v)$

47