

Objectives

- Data Compression

Feb 18, 2011

CSCI211 - Spenkle

1

Review: Encoding Problem

- Computers use bits: 0s and 1s
- Need to represent what we (humans) know to what computers know



- Map **symbol** → unique sequence of 0s and 1s
- Process is called **encoding**

Feb 18, 2011

CSCI211 - Spenkle

2

Prefix Codes

- Problem:** Encoding of one character is a *prefix* of encoding of another
- Solution: Prefix Codes:** map letters to bit strings such that *no encoding is a prefix of any other*
 - Won't need artificial devices like spaces to separate characters
- Example encodings:

a: 11	d: 10
b: 01	e: 000
c: 001	

 - Verify that no encoding is a prefix of another
 - What is **0010000011101**?

Feb 18, 2011

CSCI211 - Spenkle

3

Optimal Prefix Codes

- For typical English messages, this set of prefix codes is **not** the *optimal* set

a: 11	d: 10
b: 01	e: 000
c: 001	

- Why not?

Feb 18, 2011

CSCI211 - Spenkle

4

Optimal Prefix Codes

- For typical English messages, this set of prefix codes is **not** the *optimal* set

a: 11	d: 10
b: 01	e: 000
c: 001	

- Why not?
 - 'e' is more commonly used than other letters and should therefore have a shorter encoding

Feb 18, 2011

CSCI211 - Spenkle

5

Optimal Prefix Codes

- Goal:** minimize **Average number of Bits per Letter (ABL):**

$$\sum_{x \in S} \text{frequency of } x * \text{length of encoding of } x$$

↑
For all characters in our alphabet
- f_x : frequency that letter x occurs
- $\gamma(x)$: encoding of x
 - $|\gamma(x)|$: length of encoding of x
- Minimize **ABL** = $\sum_{x \in S} f_x |\gamma(x)|$

Feb 18, 2011

CSCI211 - Spenkle

6

Example: Calculating ABL

$f_a = .32$	a: 11
$f_b = .25$	b: 01
$f_c = .20$	c: 001
$f_d = .18$	d: 10
$f_e = .05$	e: 000

- $ABL = \sum_{x \in S} f_x |Y(x)| = ?$

Example: Calculating ABL

$f_a = .32$	a: 11
$f_b = .25$	b: 01
$f_c = .20$	c: 001
$f_d = .18$	d: 10
$f_e = .05$	e: 000

- $ABL = \sum_{x \in S} f_x |Y(x)| = ?$
- $= .32 * 2 + .25 * 2 + .20 * 3 + .18 * 2 + .05 * 2$
- $= 2.25$

Consider a fixed-length encoding:
Is it a prefix code? What is its ABL?

Fixed-Length Encodings

- Is it a prefix code?
 - Yes. Always look at fixed number of characters
- What is its ABL?
 - ABL is the length of the encoding
- For 5 characters, ABL is 3
- Variable-length prefix code's ABL (2.25) is an improvement

Can We Improve the ABL?

$f_a = .32$	a: 11
$f_b = .25$	b: 01
$f_c = .20$	c: 001
$f_d = .18$	d: 10
$f_e = .05$	e: 000

Can We Improve the ABL?

$f_a = .32$	a: 11
$f_b = .25$	b: 01
$f_c = .20$	c: 001
$f_d = .18$	d: 10
$f_e = .05$	e: 000

Swap these because c occurs more frequently than d.
Give c the shorter encoding

- $ABL = \sum_{x \in S} f_x |Y(x)| = 2.23$

Problem Statement

- Given an alphabet and a set of frequencies for the letters, produce optimal (most efficient) prefix code
 - Minimizes average # of bits per letter (ABL)

Approaches to Solution

- Brute force
 - Search space is complicated → all ways to map letters to bit strings that adhere to prefix code property
- Build towards greedy approach
 - Start: representing prefix codes


Feb 18, 2011

CSCI211 - Sprenkle

13

Binary Trees to Represent Prefix Codes

- Exposes structure better than list of mappings
 - Each leaf node is a letter
 - Follow path to the letter
 - Going left: 0
 - Going right: 1



Are these really prefix codes?
How could we show they weren't?


Feb 18, 2011

CSCI211 - Sprenkle

14

Binary Trees to Represent Prefix Codes

- Proof. If it weren't: a letter's encoding is a prefix of another letter
 - Letter is in the path of another letter
 - But, all letters are leaf nodes
 - Contradiction



Feb 18, 2011

CSCI211 - Sprenkle

15

Building the Binary Tree

- How do we build the binary tree for this mapping?
- Tree Rules:
 - Each leaf node is a letter
 - Follow path to the letter
 - Going left: 0
 - Going right: 1

Code:
a -> 1
b -> 011
c -> 010
d -> 001
e -> 000

Feb 18, 2011

CSCI211 - Sprenkle

16

Recursively Generate Tree

- All letters are in root node
- For all letters in node
 - If encoding begins with 0, letter belongs in left subtree
 - Otherwise (encoding begins with 1), letter belongs in right subtree
 - If last bit of encoding, make the letter a leaf node of that subtree
 - Shift encoding one bit
 - Process left and right children


Feb 18, 2011

CSCI211 - Sprenkle

17

Tree Properties

- What is the length of a letter's encoding?
- Define our optimal goal in tree terms




Feb 18, 2011

CSCI211 - Sprenkle

18

Tree Properties

- What is the length of a letter's encoding?
 - Length of path from root to leaf → its *depth*
- Define our optimal goal in tree terms
 - $ABL = \sum_{x \in S} f_x |Y(x)| = \sum_{x \in S} f_x \text{depth}(x)$




Feb 18, 2011

CSCI211 - Sprenkle

19

Tree Properties

- What do we want our tree to look like for the optimal solution?
 - How many leaves?
 - How many internal nodes?
 - Think about parent nodes vs. child nodes
 - When uniform frequencies?
 - Nonuniform frequencies?



Feb 18, 2011

CSCI211 - Sprenkle

20

Tree Properties

- **Claim.** The binary tree T corresponding to the optimal prefix code is *full*, i.e., each internal node has two children.
- **Proof?**


Feb 18, 2011

CSCI211 - Sprenkle

21

Tree Properties

- **Claim.** The binary tree T corresponding to the optimal prefix code is *full*, i.e., each internal node has two children.
- **Proof.** Assume that T has an internal node with only one child
 - Without loss of generality, assume left child




Feb 18, 2011

CSCI211 - Sprenkle

22

Tree Properties

- **Claim.** The binary tree T corresponding to the optimal prefix code is *full*, i.e., each internal node has two children.
- **Proof.** Assume that T has an internal node with only one child



Replace u with $v \rightarrow$ decrease depth \rightarrow original wasn't optimal

F

Toward a Solution...

- Two problems to solve:
 - Creating the prefix code tree
 - Labeling the prefix code tree with alphabet/frequencies


Feb 18, 2011

CSCI211 - Sprenkle

24

Simplifying: Know Optimal Prefix Code

- **Process:** assume knowledge of optimal solution to gain insight into finding solution
- Assume we knew the tree structure of the optimal prefix code, *how would you label the leaf nodes?*



Feb 18, 2011

CSCI211 - Sprenkle

25

Combining Our Conclusions

- The binary tree corresponding to the optimal prefix code is *full*, i.e., each internal node has two children
- We want to label the leaf nodes of the binary tree corresponding to the optimal prefix code such that nodes with *greatest depth* have *least frequency*

What does this mean the bottom of our tree looks like?

Feb 18, 2011


CSCI211 - Sprenkle

26

Combining Our Conclusions

- The binary tree corresponding to the optimal prefix code is *full*, i.e., each internal node has two children
- We want to label the leaf nodes of the binary tree corresponding to the optimal prefix code such that nodes with *greatest depth* have *least frequency*

What does this mean the bottom of our tree looks like?




Feb 18, 2011

CSCI211 - Sprenkle

27

How Can We Use This?

- Two letters with least frequency are definitely going to be siblings
 - Tie them together
 - Their parent is a "meta-letter"
 - Frequency is sum of $f_n + f_{n-1}$



Feb 18, 2011

CSCI211 - Sprenkle

28

Constructing an Optimal Prefix Code

Huffman's Algorithm:

To construct a prefix code for an alphabet S with given frequencies:

```

if  $S$  has two letters:
    Encode one letter as 0 and the other letter as 1
else:
    Replace lowest-freq letters with meta letter
    Let  $y^*$  and  $z^*$  be the two lowest-frequency letters
    Reduce Form a new alphabet  $S'$  by deleting  $y^*$  and  $z^*$  and replacing them with a new letter  $w$  of freq  $f_{y^*} + f_{z^*}$ 
    Reduce Recursively construct a prefix code  $y^j$  for  $S'$  with tree  $T'$ 
    Define a prefix code for  $S$  as follows:
    Build up Start with  $T'$ 
    Take the leaf labeled  $w$  and add two children below it labeled  $y^*$  and  $z^*$ 
    
```

Feb 18, 2011

CSCI211 - Sprenkle

29

Alternative Description

1. Create a leaf node for each symbol, labeled by its frequency, and add to a queue
2. While there is more than one node in the queue
 - a) Remove the two nodes of lowest frequency
 - b) Create a new internal node with these two nodes as children and with frequency equal to the sum of the two nodes' probabilities
 - c) Add the new node to the queue
3. The remaining node is the tree's root node

Feb 18, 2011

CSCI211 - Sprenkle

30

Creating the Optimal Prefix Code

$f_a = .32$
 $f_b = .25$
 $f_c = .20$
 $f_d = .18$
 $f_e = .05$

Feb 18, 2011

CSCI211 - Sprenkle

31

Creating the Optimal Prefix Code

$f_a = .32$
 $f_b = .25$
 $f_c = .20$
 $f_d = .18$
 $f_e = .05$

← Lowest frequencies
 ← Merge



Feb 18, 2011


CSCI211 - Sprenkle

32

Creating the Optimal Prefix Code

$f_a = .32$
 $f_b = .25$
 $f_c = .20$
 $f_{de} = .23$

← Lowest frequencies
 ← Merge



Feb 18, 2011


CSCI211 - Sprenkle

33

Creating the Optimal Prefix Code

$f_a = .32$
 $f_b = .25$
 $f_{cde} = .43$

← Lowest frequencies
 ← Merge



Feb 18, 2011

CSCI211 - Sprenkle


34

Creating the Optimal Prefix Code

$f_{ab} = .57$
 $f_{cde} = .43$

← Lowest frequencies
 ← Merge

$f_a = .32$
 $f_b = .25$
 $f_c = .20$
 $f_d = .18$
 $f_e = .05$



What are the resulting encodings?
 What is the ABL?

Feb 18, 2011


CSCI211 - Sprenkle

35

Creating the Optimal Prefix Code

a: 00
 b: 01
 c: 10
 d: 110
 e: 111

$f_a = .32$
 $f_b = .25$
 $f_c = .20$
 $f_d = .18$
 $f_e = .05$



$ABL = .32 * 2 + .25 * 2 + .20 * 2 + .18 * 3 + .05 * 3$
 $= .64 + .5 + .4 + .54 + .15$
 $= 2.23$

I chose to build the tree this way.
 What if I had switched the order of the children?

Feb 18, 2011

Implementation

- What data structures do we need?

Feb 18, 2011

CSCI211 - Spenkle

37

Implementation

- What data structures do we need?
 - Binary tree for the prefix codes
 - Priority queue for choosing the node with lowest frequency
- Where are the costs?

Feb 18, 2011

CSCI211 - Spenkle

38

Running Time

- Costs
 - Inserting and extracting node into PQ: $O(\log n)$
 - Number of insertions and extractions: $O(n)$
 - $O(n \log n)$

Feb 18, 2011

CSCI211 - Spenkle

39

Analysis of Algorithm's Optimality

- 2 page proof in book

Feb 18, 2011

CSCI211 - Spenkle

40

Real-life Compression

- Text can be compressed well because of known frequencies
- Algorithms can be optimized to languages
 - More than just "z doesn't happen very often"
 - "z doesn't happen after q"

Feb 18, 2011

CSCI211 - Spenkle

41

Assignments

- Wiki due Wednesday
 - 4.5-4.8
- PS5 due Friday after break

Feb 18, 2011

CSCI211 - Spenkle

42

Assignments

- Read, summarize Chapter 4.5-4.8
- PS5 due Friday after break
 - No class because of SSA (EC opportunity)
 - Submit somehow