

Objectives

- Analyzing algorithms
- Asymptotic running times

Jan 13, 2012

Sprenkle - CSCI211

1

Our Process

1. Understand/identify problem
 - Simplify as appropriate
2. Design a solution
3. Analyze
 - Correctness, efficiency
 - May need to go back to step 2 and try again
4. Implement (On Monday)
 - Within bounds shown in analysis

Jan 13, 2012

Sprenkle - CSCI211

2

Computational Tractability

As soon as an Analytic Engine exists, it will necessarily guide the future course of the science. Whenever any result is sought by its aid, the question will arise - By what course of calculation can these results be arrived at by the machine in the shortest time?

-- Charles Babbage



Charles Babbage
(1864)



Analytic Engine
(schematic)

Jan 13, 2012

Sprenkle - CSCI211

<http://plan28.org/>

3

**TODAY'S GOAL:
DEFINE ALGORITHM
EFFICIENCY**

Jan 13, 2012

Sprenkle - CSCI211

4

Brute Force

- For many non-trivial problems, there is a natural brute force search algorithm that checks every possible solution
 - Typically takes 2^N time or worse for inputs of size N
 - Unacceptable in practice

Example: How many possible solutions are there in the stable matching problem?

In other words, how many possible *perfect* matchings are there? For each perfect match, we'll check if it's stable.

Jan 13, 2012

Sprenkle - CSCI211

5

Brute Force

- For many non-trivial problems, there is a natural brute force search algorithm that checks every possible solution
 - Typically takes 2^N time or worse for inputs of size N
 - Unacceptable in practice
- Example: Stable matching: $n!$ with n men and n women
 - If n increases by 1, what happens to the running time?

Jan 13, 2012

Sprenkle - CSCI211

6

How Do We Measure Runtime?

Jan 13, 2012

Sprenkle - CSCI211

7

Worst-Case Running Time

- Obtain bound on *largest possible* running time of algorithm on input of a given size N
 - Generally captures efficiency in practice
 - Draconian view but hard to find effective alternative

What are alternatives to worst-case analysis?

Jan 13, 2012

Sprenkle - CSCI211

8

Average Case Running Time

- Obtain bound on running time of algorithm on *random* input as a function of input size N
 - Hard (or impossible) to accurately model real instances by random distributions
 - Algorithm tuned for a certain distribution may perform poorly on other inputs

Jan 13, 2012

Sprenkle - CSCI211

9

Towards a Definition of Efficient...

- **Desirable scaling property:** When input size doubles, algorithm should only slow down by some constant factor C
 - Doesn't grow multiplicatively

Jan 13, 2012

Sprenkle - CSCI211

10

Polynomial-Time

Defn. There exists constants $c > 0$ and $d > 0$ such that on every input of size N , its running time is bounded by $c N^d$ steps.

- ✓ **Desirable scaling property:** When input size doubles, algorithm should only slow down by some constant factor C
 - What happens if we double N ?
- **Defn.** An algorithm is *polynomial time* (or *polytime*) if the above scaling property holds.

Jan 13, 2012

Sprenkle - CSCI211

11

Algorithm Efficiency

- **Defn.** An algorithm is *efficient* if its running time is *polynomial*
- **Justification:** It really works in practice!
 - In practice, poly-time algorithms that people develop almost always have low constants and low exponents
 - Breaking through the exponential barrier of brute force typically exposes some crucial structure of the problem
- **Exceptions**
 - Some poly-time algorithms do have high constants and/or exponents ($6.02 \times 10^{23} \times N^{20}$) and are useless in practice
 - Some exponential-time (or worse) algorithms are widely used because the worst-case instances seem to be rare

Jan 13, 2012

Sprenkle - CSCI211

12

Running Times

Table 2.1 The running times (rounded up) of different algorithms on inputs of increasing size, for a processor performing a million high-level instructions per second. In cases where the running time exceeds 10^{25} years, we simply record the algorithm as taking a very long time.

Input Size	n	$n \log_2 n$	n^2	n^3	1.5^n	2^n	$n!$
$n = 10$	< 1 sec	< 1 sec	< 1 sec	< 1 sec	< 1 sec	< 1 sec	4 sec
$n = 30$	< 1 sec	< 1 sec	< 1 sec	< 1 sec	< 1 sec	18 min	10^{25} years
$n = 50$	< 1 sec	< 1 sec	< 1 sec	< 1 sec	11 min	36 years	very long
$n = 100$	< 1 sec	< 1 sec	< 1 sec	1 sec	12,892 years	10^{17} years	very long
$n = 1,000$	< 1 sec	< 1 sec	1 sec	18 min	very long	very long	very long
$n = 10,000$	< 1 sec	< 1 sec	2 min	12 days	very long	very long	very long
$n = 100,000$	< 1 sec	2 sec	3 hours	32 years	very long	very long	very long
$n = 1,000,000$	1 sec	20 sec	12 days	31,710 years	very long	very long	very long


Polynomial

Jan 13, 2012

Sprengle - CSCI211

13

Visualizing Running Times




- Huge difference from polynomial to not polynomial
- Differences in runtime matter more as input size increases

Jan 13, 2012

Sprengle - CSCI211

14

Comparing 10000 n^2 and n^3



- As input size increases, n^3 dominates large constant $\cdot n^2$
- Care about running time as input size approaches infinity
- Only care about highest-order term

Jan 13, 2012

Sprengle - CSCI211

15

Asymptotic Order of Growth: Upper Bounds

- $T(n)$ is the worst case running time of an algorithm
- We say that $T(n)$ is $O(f(n))$ if there exist constants $c > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$, we have $T(n) \leq c \cdot f(n)$


→ T is **asymptotically upperbounded** by f

Jan 13, 2012

Sprengle - CSCI211

16

Asymptotic Order of Growth: Upper Bounds



Jan 13, 2012

Sprengle - CSCI211

17

Upper Bounds Example

- Find an upperbound for $T(n) = pn^2 + qn + r$
- p, q, r are positive constants

Idea: Let's inflate the terms in the equation so that all terms are n^2

Jan 13, 2012

Sprengle - CSCI211

18

Upper Bounds Example

- $T(n) = pn^2 + qn + r$
 - p, q, r are positive constants
 - For all $n \geq 1$,

$$\begin{aligned} T(n) &= pn^2 + qn + r \\ &\leq pn^2 + qn^2 + rn^2 \\ &= (p+q+r) n^2 \\ &= c n^2 \end{aligned}$$
- ➔ $T(n) \leq cn^2$, where $c = p+q+r$
 ➔ $T(n) = O(n^2)$
 • Also correct to say that $T(n) = O(n^3)$

Notation

- $T(n) = O(f(n))$ is a **slight abuse of notation**
 - Asymmetric:
 - $f(n) = 5n^3; g(n) = 3n^2$
 - $f(n) = O(n^3) = g(n)$
 - But $f(n) \neq g(n)$.
 - **Better notation:** $T(n) \in O(f(n))$
- **Meaningless statement.** Any comparison-based sorting algorithm requires *at least* $O(n \log n)$ comparisons
 - Use Ω for lower bounds

Asymptotic Order of Growth: Lower Bounds

- Complementary to upper bound
- $T(n)$ is $\Omega(f(n))$ if there exist constants $\epsilon > 0$ and $n_0 \geq 0$ such that for all $n \geq n_0$, we have

$T(n) \geq \epsilon \cdot f(n)$

➔ T is **asymptotically lowerbounded** by f

Example: Lower Bound

- $T(n) = pn^2 + qn + r$
 - p, q, r are positive constants
- **Idea:** *Deflate* terms rather than inflate
- For all $n \geq 0$,

$$\begin{aligned} T(n) &= pn^2 + qn + r \geq pn^2 \\ \rightarrow T(n) &\geq \epsilon n^2, \text{ where } \epsilon = p > 0 \\ \rightarrow T(n) &= \Omega(n^2) \end{aligned}$$
- Also correct to say that $T(n) = \Omega(n)$

Tight bounds

$T(n)$ is $\Theta(f(n))$ if $T(n)$ is both $O(f(n))$ and $\Omega(f(n))$

➢ The "right" bound


A Fashion Analogy

- O == Hammer pants
 - Loose and baggy with plenty of room for the pants to shrink or the body to grow
- Ω == The pants you plan to fit in this summer after working off the snacks from Christmas
- Θ == Katy Perry's skin tight jeans in a teenage dream
 - Can't make them any smaller, and no extra room to even fit a cell phone in the pocket

Property: Transitivity

- If $f = O(g)$ and $g = O(h)$ then $f = O(h)$
- If $f = \Omega(g)$ and $g = \Omega(h)$ then $f = \Omega(h)$
- If $f = \Theta(g)$ and $g = \Theta(h)$ then $f = \Theta(h)$

Proofs in book



Jan 13, 2012 Sprenkle - CSCI211 25

Property: Additivity

- If $f = O(h)$ and $g = O(h)$ then $f + g = O(h)$
- If $f = \Omega(h)$ and $g = \Omega(h)$ then $f + g = \Omega(h)$
- If $f = \Theta(h)$ and $g = \Theta(h)$ then $f + g = \Theta(h)$

Proofs in book

Sketch proof for O:
 By defn, $f \leq c \cdot h$
 By defn, $g \leq d \cdot h$
 $f + g \leq c \cdot h + d \cdot h = (c + d)h = c' \cdot h$
 $\rightarrow f + g$ is $O(h)$

Jan 13, 2012 Sprenkle - CSCI211 26

Practice: Asymptotic Order of Growth

What are the upper bounds, lower bounds, and tight bound on $T(n)$?

- $T(n) = 32n^2 + 17n + 32$

Jan 13, 2012 Sprenkle - CSCI211 27

Practice: Asymptotic Order of Growth

- $T(n) = 32n^2 + 17n + 32$
 - $T(n)$ is $O(n^2)$, $O(n^3)$, $\Omega(n^2)$, $\Omega(n)$, and $\Theta(n^2)$
 - $T(n)$ is **not** $O(n)$, $\Omega(n^3)$, $\Theta(n)$, or $\Theta(n^3)$

Jan 13, 2012 Sprenkle - CSCI211 28

ASYMPTOTIC BOUNDS FOR CLASSES OF ALGORITHMS

Jan 13, 2012 Sprenkle - CSCI211 29

Asymptotic Bounds for Polynomials

- $a_0 + a_1n + \dots + a_d n^d \in \Theta(n^d)$ if $a_d > 0$
 - ➔ Runtime determined by higher-order term
- **Polynomial time.** Running time is $O(n^d)$ for some constant d that is independent of the input size n
- Other examples of polynomial times:
 - $O(n^{1/2})$
 - $O(n^{1.58})$
 - $O(n \log n) \leq O(n^2)$

Jan 13, 2012 Sprenkle - CSCI211 30

Asymptotic Bounds for Logarithms

- **Logarithms.** $\log_b n = x$, where $b^x = n$
 - Approximate: To represent n in base- b , need $x+1$ digits

N	b	x
100	10	
1000	10	
100	2	
1000	2	

Jan 13, 2012

Sprenkle - CSCI211

31

Asymptotic Bounds for Logarithms

- **Logarithms.** $\log_b n = x$, where $b^x = n$
 - Approximate: To represent n in base- b , need $x+1$ digits

N	b	x
100	10	2
1000	10	3
100	2	6.64
1000	2	9.92

Describe the running time of an $O(\log n)$ algorithm as the input size grows. Compare with polynomials.


Jan 13, 2012

Sprenkle - CSCI211

32

Asymptotic Bounds for Logarithms

- **Logarithms.** $\log_b n = x$, where $b^x = n$
 - x is number of digits to represent n in base- b representation



Jan 1

33

Asymptotic Bounds for Logarithms

- **Logarithms.** $\log_b n = x$, where $b^x = n$

➔ Slowly growing functions

- Identity: $\log_a n = \log_b n / \log_b a$

➤ Means that

$$\log_a n = 1/\log_b a * \log_b n$$

Constant!

- $O(\log_a n) = O(\log_b n)$ for any constants $a, b > 0$

Jan 13, 2012

Sprenkle - CSCI211

34

Asymptotic Bounds for Logarithms

- **Logarithms.** $\log_b n = x$, where $b^x = n$
 - ➔ Slowly growing functions
- $O(\log_a n) = O(\log_b n)$ for any constants $a, b > 0$
 - ➔ Don't need to specify the base
- For every $x > 0$, $\log n = O(n^x)$
 - ➔ Log grows slower than every polynomial

Jan 13, 2012

Sprenkle - CSCI211

35

Asymptotic Bounds for Exponentials

- **Exponentials:** functions of the form $f(n) = r^n$ for constant base r
 - Faster growth rates as n increases
- For every $r > 1$ and every $d > 0$, $r^n = O(n^d)$
 - ➔ Every exponential grows faster than every polynomial

Jan 13, 2012

Sprenkle - CSCI211

36

Summary of Asymptotic Bounds

- In terms of growth rates

Logarithms < Polynomials < Exponentials

Jan 13, 2012

Sprengle - CSCI211

37

A SURVEY OF COMMON RUNNING TIMES

Jan 13, 2012

Sprengle - CSCI211

38

Linear Time: $O(n)$

- Running time is at most a **constant** factor times the size of the input
- Example.** Computing the maximum:
Compute maximum of n numbers a_1, \dots, a_n

```

max = a1
for i = 2 to n
  if (ai > max)
    max = ai
    
```

} **Constant** work for each input (does not depend on n)


Jan 13, 2012

Sprengle - CSCI211

39

Example Linear Time: $O(n)$

- Merge:** Combine two sorted lists $A = a_1, a_2, \dots, a_n$ with $B = b_1, b_2, \dots, b_n$ into sorted whole



Jan 13, 2012

Sprengle - CSCI211

40

Example Linear Time: $O(n)$

- Merge:** Combine two sorted lists $A = a_1, a_2, \dots, a_n$ with $B = b_1, b_2, \dots, b_n$ into sorted whole
- Claim.** Merging two lists of size n takes $O(n)$ time

```

i = 1, j = 1
while (both lists are nonempty)
  if (ai ≤ bj)
    append ai to output list and increment i
  else (ai > bj)
    append bj to output list and increment j
append remainder of nonempty list to output list
    
```

Jan 13, 2012

Sprengle - CSCI211

41

Example Linear Time: $O(n)$

- Merge:** Combine two sorted lists $A = a_1, a_2, \dots, a_n$ with $B = b_1, b_2, \dots, b_n$ into sorted whole
- Claim.** Merging two lists of size n takes $O(n)$ time
- Proof.** After each comparison, the length of output list increases by 1

```

i = 1, j = 1
while (both lists are nonempty)
  if (ai ≤ bj)
    append ai to output list and increment i
  else (ai > bj)
    append bj to output list and increment j
append remainder of nonempty list to output list
    
```

42

$O(n \log n)$ Time

- Also referred to as *linearithmic* time
- Arises in divide-and-conquer algorithms
 - Splitting input into equal pieces, solve recursively, combine solutions in linear time

What well-known set of algorithms has an $O(n \log n)$ running time?

Jan 13, 2012

Sprenkle - CSCI211

43

$O(n \log n)$ Time Example

- **Sorting:** Mergesort and heapsort are sorting algorithms that perform $O(n \log n)$ comparisons
- **Mergesort**
 1. Break input into equal-sized pieces
 2. Sorts each half recursively
 3. Merges sorted halves into a sorted list

Talk about the bound on running time later...

Jan 13, 2012

Sprenkle - CSCI211

44

$O(n \log n)$ Time Example

- **Largest empty interval.** Given n (not necessarily ordered) time-stamps x_1, \dots, x_n at which copies of a file arrive at a server, what is largest interval of time when no copies of the file arrive?

Jan 13, 2012

Sprenkle - CSCI211

45

$O(n \log n)$ Time Example

- **Largest empty interval.** Given n (not necessarily ordered) time-stamps x_1, \dots, x_n at which copies of a file arrive at a server, what is largest interval of time when no copies of the file arrive?
- **$O(n \log n)$ solution**
 1. Sort time-stamps
 2. Scan sorted list in order, identifying the maximum gap between successive time-stamps

Jan 13, 2012

Sprenkle - CSCI211

46

Quadratic Time: $O(n^2)$

- Examples?

Jan 13, 2012

Sprenkle - CSCI211

47

Quadratic Time: $O(n^2)$

- **Examples:**
 - Enumerate all pairs of elements
 - Often involves nested loops (n iterations)

Jan 13, 2012

Sprenkle - CSCI211

48

Quadratic Time: $O(n^2)$

- **Closest pair of points.** Given a list of n points in the plane $(x_1, y_1), \dots, (x_n, y_n)$, find the pair that is closest
- **$O(n^2)$ solution.** Try all pairs of points

```

min = (x1 - x2)2 + (y1 - y2)2
for i = 1 to n
  for j = i+1 to n
    d = (xi - xj)2 + (yi - yj)2
    if (d < min)
      min = d
  
```

← don't need to take square roots

$\Omega(n^2)$ seems inevitable, but Chapter 5 has an $O(n \log n)$ solution

Jan 13, 2012

Sprenkle - CSCI211

49

Assignments

- Continue reading Chapter 2
 - Covering later sections on Monday
- Journal for Chapter 1-2.2 due Tuesday
- Problem Set 1 due next Friday in class
 - Start early!
 - Read problems and let your brain start thinking about them
 - Proof, stable matching, asymptotic bounds

Jan 13, 2012

Sprenkle - CSCI211

50