

## Objectives

Dynamic Programming

- Shortest paths
- Distance Vector Protocol

Network flow

- Maximum flow
- Minimum cuts

Mar 30, 2009 CS211 1

## SHORTEST PATHS

2

## Shortest Paths

Given a directed graph  $G = (V, E)$ , with edge weights  $c_{vw}$ , find shortest path from node  $s$  to node  $t$

*allow negative weights*

Allows modeling other phenomena

Mar 30, 2009 CS211 3

## Shortest Paths: Failed Attempts

Dijkstra. Can fail if negative edge costs

Mar 30, 2009 CS211 4

## Shortest Paths: Failed Attempts

Dijkstra. Can fail if negative edge costs

Re-weighting. Adding a constant to every edge weight can fail

Why?

Mar 30, 2009 CS211 5

## Shortest Paths: Negative Cost Cycles

If some path from  $s$  to  $t$  contains a negative cost cycle, there does **not** exist a shortest  $s$ - $t$  path


Why?

Otherwise, there exists one that is *simple* (i.e., does not repeat nodes)

- What does this mean about number of edges in path?

Mar 30, 2009 CS211 6

### Shortest Paths: Negative Cost Cycles



If some path from  $s$  to  $t$  contains a negative cost cycle, there does **not** exist a shortest  $s$ - $t$  path  
 Otherwise, there exists one that is *simple* (i.e., does not repeat nodes)

- Path has at most  $n-1$  edges, where  $n$  is # of nodes in graph


### Towards a Recurrence

$OPT(i, v)$ : minimum cost of a  $v$ - $t$  path  $P$  using at most  $i$  edges

- This formulation eases later discussion

Original problem is  $OPT(n-1, s)$

Break down into subproblems based on  $i$  and  $v$



### Shortest Paths: Dynamic Programming

Def.  $OPT(i, v)$  = minimum cost of a  $v$ - $t$  path  $P$  using at most  $i$  edges

- Case 1:  $P$  uses at most  $i-1$  edges
  - $OPT(i, v) = OPT(i-1, v)$
- Case 2:  $P$  uses exactly  $i$  edges
  - if  $(v, w)$  is first edge, then  $OPT$  uses  $(v, w)$ , and then selects best  $w$ - $t$  path using at most  $i-1$  edges
  - Cost: cost of chosen edge

$$OPT(i, v) = \begin{cases} 0 & \text{if } i = 0 \\ \min \left\{ OPT(i-1, v), \min_{(v,w) \in E} \{ OPT(i-1, w) + c_{vw} \} \right\} & \text{otherwise} \end{cases}$$

### Shortest Paths: Implementation

```

Shortest-Path(G, t)
n = number of nodes in G
foreach node v ∈ V
    M[0, v] = ∞ # infinite cost to reach all nodes
M[0, t] = 0 # no cost to reach destination from dest

for i = 1 to n-1
    foreach node v ∈ V
        M[i, v] = M[i-1, v] # at most cost of 1 less
        foreach edge (v, w) ∈ E
            M[i, v] = min(M[i, v], M[i-1, w] + cvw)
    
```

Shortest path is  $M[n-1, s]$

Starting node

Cost of chosen edge

Analysis?

### Shortest Paths: Implementation

```


Shortest-Path(G, t)
n = number of nodes in G
foreach node v ∈ V
    M[0, v] = ∞ # infinite cost to reach all nodes
M[0, t] = 0 # no cost to reach destination from dest

for i = 1 to n-1
    foreach node v ∈ V
        M[i, v] = M[i-1, v] # at most cost of 1 less
        foreach edge (v, w) ∈ E
            M[i, v] = min(M[i, v], M[i-1, w] + cvw)
    
```

$O(n^3)$

Shortest path is  $M[n-1, s]$


### Example



	0	1	2	3	4	5
t	0	0	0	0	0	0
a	∞					
b	∞					
c	∞					
d	∞					
e	∞					

What edges do we need to look at for each node?

### Example




Edges

- b, t
- d, e
- b, t
- a, t
- c, t

	0	1	2	3	4	5
t	0	0	0	0	0	0
a	∞					
b	∞					
c	∞					
d	∞					
e	∞					

Mar 30, 2009 CS211 13

### Example




Edges

- b, t
- d, e
- b, t
- a, t
- c, t

	0	1	2	3	4	5
t	0	0	0	0	0	0
a	∞	-3				
b	∞	∞				
c	∞	3				
d	∞	4				
e	∞	2				

Mar 30, 2009 CS211 14

### Example




Edges

- b, t
- d, e
- b, t
- a, t
- c, t

	0	1	2	3	4	5
t	0	0	0	0	0	0
a	∞	-3	-3			
b	∞	∞	0			
c	∞	3	3			
d	∞	4	3			
e	∞	2	0			

Mar 30, 2009 CS211 15

### Example




Edges

- b, t
- d, e
- b, t
- a, t
- c, t

	0	1	2	3	4	5
t	0	0	0	0	0	0
a	∞	-3	-3	-4		
b	∞	∞	0	-2		
c	∞	3	3	3		
d	∞	4	3	3		
e	∞	2	0	0		

Mar 30, 2009 CS211 16

### Example




Edges

- b, t
- d, e
- b, t
- a, t
- c, t

	0	1	2	3	4	5
t	0	0	0	0	0	0
a	∞	-3	-3	-4	-6	
b	∞	∞	0	-2	-2	
c	∞	3	3	3	3	
d	∞	4	3	3	2	
e	∞	2	0	0	0	

Mar 30, 2009 CS211 17

### Example



Edges

- b, t
- d, e
- b, t
- a, t
- c, t

	0	1	2	3	4	5
t	0	0	0	0	0	0
a	∞	-3	-3	-4	-6	-6
b	∞	∞	0	-2	-2	-2
c	∞	3	3	3	3	3
d	∞	4	3	3	2	0
e	∞	2	0	0	0	0

Mar 30, 2009 CS211 18

## Based on Example Experience

What could we do to improve the algorithm's runtime/space requirements?

Mar 30, 2009

CS211

19

## Shortest Paths: Practical Improvements

### Practical improvements

- Maintain only one array  $M[v]$  = shortest  $v$ - $t$  path that we have found so far
- No need to check edges of the form  $(v, w)$  *unless*  $M[w]$  changed in previous iteration

**Theorem.** Throughout algorithm,  $M[v]$  is length of some  $v$ - $t$  path, and after  $i$  rounds of updates, the value  $M[v]$  is no larger than the length of shortest  $v$ - $t$  path using  $\leq i$  edges.

### Overall impact

- Memory:  $O(m + n)$
- Running time:  $O(mn)$  worst case but substantially faster in practice

Mar 30, 2009

CS211

20

## Bellman-Ford: Efficient Implementation

```

Push-Based-Shortest-Path(G, s, t)
  foreach node v ∈ V
    M[v] = ∞
    successor[v] = φ

  M[t] = 0
  for i = 1 to n-1
    foreach node w ∈ V
      if M[w] has been updated in previous iteration
        foreach node v such that (v, w) ∈ E
          if M[v] > M[w] + cvw
            M[v] = M[w] + cvw
            successor[v] = w

  If no M[w] value changed in iteration i, stop.
    
```

Mar 30, 2009

CS211

21

## DISTANCE VECTOR PROTOCOL

22

## Problem Context

Application of shortest-path problem: *routers in communication network find most efficient path to destination*

Model of communication network

- Nodes ≈ routers
- Edge ≈ direct communication link
- Cost of edge ≈ delay on link ← *Naturally nonnegative*

Possible solution: Dijkstra's algorithm

Mar 30, 2009

CS211

23

## Distance Vector Protocol

### Model of communication network

- Nodes ≈ routers; Edge ≈ direct communication link
- Cost of edge ≈ delay on link ← *Naturally nonnegative but Bellman-Ford used anyway!*

**Dijkstra's algorithm.** Requires *global* information of network

**Bellman-Ford.** Uses only local knowledge of neighboring nodes

- **Distribute algorithm:** each node  $v$  maintains its value  $M[v]$ 
  - Updates its value after getting neighbor's values:
    - $\min_{w \in V} (c_{vw} + M[w])$

Mar 30, 2009

CS211

24

## Distance Vector Protocol

Each router maintains a vector of **shortest path lengths** to every other node (distances) and the **first hop** on each path (directions)

**Algorithm:** each router performs  $n$  separate computations, one for each potential destination node

**Synchronization.** We don't expect routers to run in lockstep. The order in which each **foreach** loop executes is not important. Moreover, algorithm still converges even if updates are asynchronous.

"Routing by rumor."

Used in many routers, e.g. RIP, Xerox XNS RIP, Novell's IPX RIP, ...

Mar 30, 2009

CS211

25

## Issues with Distance Vector Protocol

Original algorithm developed for one central machine; costs known in advance, didn't change

Edge costs may **change** during algorithm (or fail completely)



Mar 30, 2009

CS211

26

## Path Vector Protocols

Link state routing

- Each router stores the *entire path*
  - Not just the distance and the first hop
- Based on Dijkstra's algorithm
- Avoids "counting-to-infinity" problem and related difficulties
- Requires significantly more storage

Ex. Border Gateway Protocol (BGP), Open Shortest Path First (OSPF)

Mar 30, 2009

CS211

27

## NETWORK FLOW


Mar 30, 2009

CS211

28

## Soviet Rail Network, 1955

44 vertices  
105 edges



Reference: *On the history of the transportation and maximum flow problems.*  
Alexander Schrijver in *Math Programming*, 91: 3, 2002.

Mar 30, 2009

CS211

29

## Maximum Flow and Minimum Cut

Two very rich algorithmic problems

Cornerstone problems in combinatorial optimization

Beautiful mathematical duality

Nontrivial applications / reductions

- Data mining
- Open-pit mining
- Project selection
- Airline scheduling
- Bipartite matching
- Baseball elimination
- Image segmentation
- Network connectivity
- Network reliability
- Distributed computing
- Egalitarian stable matching
- Security of statistical data
- Network intrusion detection
- Multi-camera scene reconstruction
- Many many more . . .

30

### Flow Network

Abstraction for material *flowing* through the edges  
 $G = (V, E)$  = directed graph, no parallel edges  
 Two distinguished nodes:  $s$  = source,  $t$  = sink  
 $c(e)$  = capacity of edge  $e$ ,  $> 0$

What is special about the source and sink?

Mar 30, 2009 CS211 31

### Flows

An **s-t flow** is a function that satisfies

- Capacity condition: For each  $e \in E$ :  $0 \leq f(e) \leq c(e)$
- Conservation condition: For each  $v \in V - \{s, t\}$ :  $\sum_{e \text{ into } v} f(e) = \sum_{e \text{ out of } v} f(e)$

Flow can't exceed capacity

Flow in == Flow out

Mar 30, 2009 CS211 32

### Flows

The **value** of a flow  $f$  is  $v(f) = \sum_{e \text{ out of } s} f(e)$

Mar 30, 2009 CS211 33

### Maximum Flow Problem

Make network most efficient

- Use most of available capacity

**Goal:** Find s-t flow of maximum value

Check satisfies constraints

Mar 30, 2009 CS211 34

### Cuts

An **s-t cut** is a partition  $(A, B)$  of  $V$  with  $s \in A$  and  $t \in B$

The **capacity** of a cut  $(A, B)$  is  $cap(A, B) = \sum_{e \text{ out of } A} c(e)$

Capacity = 10 + 5 + 15 = 30

Mar 30, 2009 CS211 35

### Cuts

An **s-t cut** is a partition  $(A, B)$  of  $V$  with  $s \in A$  and  $t \in B$

The **capacity** of a cut  $(A, B)$  is  $cap(A, B) = \sum_{e \text{ out of } A} c(e)$

Capacity = 9 + 15 + 8 + 30 = 62

Mar 30, 2009 CS211 36

