

Objectives

- Network Flow
 - Max flow
 - Min cut

Mar 28, 2012

CSCI211 - Sprenkle

1

Dynamic Programming Wrapup

- What we didn't cover
 - 6.5: RNA Secondary Structure: Dynamic Programming Over Intervals
 - 6.9: Shortest Paths and Distance Vector Protocols
 - In practice

Mar 28, 2012

CSCI211 - Sprenkle

2

Motivating Flow Network Problems

- Modeling *transportation* networks
 - Edges: carry traffic
 - Nodes: pass traffic between edges
- Can represent many different types of problems
 - Instead of looking at all possibilities, formulate as a flow problem


Mar 28, 2012

CSCI211 - Sprenkle

3

Flow Network

- $G = (V, E)$ = directed graph, no parallel edges
- Two distinguished nodes: s = source, t = sink
- $c(e)$ = capacity of edge e , > 0




Mar 28, 2012

CSCI211 - Sprenkle

4

Flows

- An **s-t flow** is a function that satisfies
 - **Capacity condition:** For each $e \in E$: $0 \leq f(e) \leq c(e)$
 - **Conservation condition:** For each $v \in V - \{s, t\}$: $\sum_{e \text{ into } v} f(e) = \sum_{e \text{ out of } v} f(e)$




Mar 28, 2012

CSCI211 - Sprenkle

5

Flows

- The **value** of a flow f is $v(f) = \sum_{e \text{ out of } s} f(e)$



Mar 28, 2012


CSCI211 - Sprenkle

6

Maximum Flow Problem


- Make network most efficient
 - Use most of available capacity

Goal: Find s - t flow of maximum value




Towards a Max Flow Algorithm

- Greedy algorithm
 - Start all edges $e \in E$ at $f(e) = 0$
 - Find an s - t path P with the most capacity: $f(e) < c(e)$
 - Augment flow along path P
 - Repeat until you get stuck



Towards a Max Flow Algorithm


- Greedy algorithm
 - Start all edges $e \in E$ at $f(e) = 0$
 - Find an s - t path P with the most capacity: $f(e) < c(e)$
 - Augment flow along path P
 - Repeat until you get stuck



Towards a Max Flow Algorithm

- Greedy algorithm
 - Start all edges $e \in E$ at $f(e) = 0$
 - Find an s - t path P with the most capacity: $f(e) < c(e)$
 - Augment flow along path P
 - Repeat until you get stuck

locally optimality does not \Rightarrow global optimality



Towards a solution...

RESIDUAL GRAPHS


Towards a Residual Graph

- Original edge: $e = (u, v) \in E$
 - Flow $f(e)$, capacity $c(e)$




Towards a Residual Graph

- Original edge: $e = (u, v) \in E$
 - Flow $f(e)$, capacity $c(e)$
- Residual edge
 - $e = (u, v)$ w/ capacity $c(e) - f(e)$
 - $e^R = (v, u)$ with capacity $f(e)$
 - To undo flow



Residual Graph: G_f

- Original edge: $e = (u, v) \in E$
 - Flow $f(e)$, capacity $c(e)$
- Residual edge
 - $e = (u, v)$ w/ capacity $c(e) - f(e)$
 - $e^R = (v, u)$ with capacity $f(e)$
 - To undo flow
- Residual graph: $G_f = (V, E_f)$
 - Residual edges with positive residual capacity
 - $E_f = \{e : f(e) < c(e)\} \cup \{e^R : f(e) > 0\}$
 - Forward edges
 - Backward edges



Applying Residual Graph

- Used to find the maximum flow
 - Use similar idea to greedy algorithm
- Residual path: simple $s-t$ path in G_f
 - Also known as augmenting path

Augmenting Path Algorithm

$c = \text{capacity}$

```

Ford-Fulkerson( $G, s, t, c$ )
  foreach  $e \in E$   $f(e) = 0$  # initially no flow
   $G_f = \text{residual graph}$ 


  while there exists augmenting path  $P$ 
     $f = \text{Augment}(f, c, P)$  # change the flow
    update  $G_f$  # build a new residual graph

  return  $f$ 
    
```


```

Augment( $f, c, P$ )
   $b = \text{bottleneck}(P)$  # edge on  $P$  with least capacity
  foreach  $e \in P$ 
    if ( $e \in E$ )  $f(e) = f(e) + b$  # forward edge, ↑ flow
    else  $f(e^R) = f(e) - b$  # forward edge, ↓ flow
  return  $f$ 
    
```

Ford-Fulkerson Algorithm




Ford-Fulkerson Algorithm




What does the residual graph look like?

Ford-Fulkerson Algorithm




Mar 28, 2012 CSC1211 - Sprenkle 19

Ford-Fulkerson Algorithm




Mar 28, 2012 CSC1211 - Sprenkle 20

Ford-Fulkerson Algorithm




Mar 28, 2012 CSC1211 - Sprenkle 21

Ford-Fulkerson Algorithm




Mar 28, 2012 CSC1211 - Sprenkle 22

Ford-Fulkerson Algorithm





Mar 28, 2012 CSC1211 - Sprenkle 23

Ford-Fulkerson Algorithm



Mar 28, 2012 CSC1211 - Sprenkle 24



Ford-Fulkerson Algorithm



Mar 28, 2012

CSCI211 - Sp

Ford-Fulkerson Algorithm



Mar 28, 2012

CSCI211 - Sprenkle

26

Analyzing Augmenting Path Algorithm

```

Ford-Fulkerson(G, s, t, c)
  foreach e ∈ E f(e) = 0 # initially no flow
  G_f = residual graph

  while there exists augmenting path P
    f = Augment(f, c, P) # change the flow
    update G_f # build a new residual graph

  return f
    
```

```

Augment(f, c, P)
  b = bottleneck(P) # edge on P with least capacity
  foreach e ∈ P
    if (e ∈ E) f(e) = f(e) + b # forward edge, ↑ flow
    else f(e*) = f(e) - b # backward edge, ↓ flow
  return f
    
```

Why does alg work? What is happening at each iteration?
 What is the running time? Need more analysis ...

Mar 28, 2012

Need more analysis ...

MINIMUM CUTS

Mar 28, 2012


CSCI211 - Sprenkle

28

Cuts

- An **s-t cut** is a partition (A, B) of V with s ∈ A and t ∈ B
- The **capacity** of a cut (A, B) is $cap(A, B) = \sum_{e \text{ out of } A} c(e)$

What is the capacity of this cut?



Mar 28, 2012


CSCI211 - Sprenkle

29

Minimum Cut Problem

- Find an **s-t cut** of **minimum capacity**
- ↳ Puts **upperbound** on maximum flow

Same graph, different cut




Mar 28, 2012

CSCI211 - Sprenkle

30

Recall


- The **value** of a flow f is $v(f) = \sum_{e \text{ out of } s} f(e)$



Flow Value Lemma


- Let f be any flow, and let (A, B) be any s - t cut. Then, the value of the flow is $= f^{\text{out}}(A) - f^{\text{in}}(A)$.

What is the value of this flow?



Flow Value Lemma

- Let f be any flow, and let (A, B) be any s - t cut. Then, the value of the flow is $= f^{\text{out}}(A) - f^{\text{in}}(A)$.



Flow Value Lemma

- Let f be any flow, and let (A, B) be any s - t cut.

- Then $\sum_{e \text{ out of } A} f(e) - \sum_{e \text{ in to } A} f(e) = v(f)$.


Pf. $v(f) = \sum_{e \text{ out of } s} f(e)$ By definition

$$= \sum_{v \in A} \left(\sum_{e \text{ out of } v} f(e) - \sum_{e \text{ in to } v} f(e) \right)$$

by flow conservation, all terms except $v = s$ are 0


$$= \sum_{e \text{ out of } A} f(e) - \sum_{e \text{ in to } A} f(e)$$

- Possibilities for edge e :
- Both ends in A (0)
 - Points out from A (+)
 - Points in to A (-)



Weak Duality

- Let f be any flow and let (A, B) be any s - t cut. Then the value of the flow is **at most** the cut's capacity



Weak Duality

- Let f be any flow. Then, for any s - t cut (A, B) $v(f) \leq \text{cap}(A, B)$.


Pf.

By FVL $v(f) = \sum_{e \text{ out of } A} f(e) - \sum_{e \text{ in to } A} f(e)$

$$\leq \sum_{e \text{ out of } A} f(e)$$


$$\leq \sum_{e \text{ out of } A} c(e)$$

$$= \text{cap}(A, B)$$



Certificate of Optimality

- **Corollary.** Let f be any flow, and let (A, B) be any cut. If $v(f) = \text{cap}(A, B)$, then f is a **max flow** and (A, B) is a **min cut**.



Mar 28, 2012

37

Recall: Residual Graph G_f

- **Original edge:** $e = (u, v) \in E$
 - Flow $f(e)$, capacity $c(e)$
- **Residual edge**
 - $e = (u, v)$ w/ capacity $c(e) - f(e)$
 - $e^R = (v, u)$ with capacity $f(e)$
 - To undo flow
- **Residual graph:** $G_f = (V, E_f)$
 - Residual edges with *positive* residual capacity
 - $E_f = \{e : f(e) < c(e)\} \cup \{e^R : f(e) > 0\}$

Mar 28, 2012

CSCI211 - Sprenkle

38

Recall: Augmenting Path Algorithm

```

Ford-Fulkerson(G, s, t, c)
  foreach e in E f(e) = 0 # initially no flow
  G_f = residual graph

  while there exists augmenting path P
    f = Augment(f, c, P) # change the flow
    update G_f # build a new residual graph

  return f
    
```

```

Augment(f, c, P)
  b = bottleneck(P) # edge on P with least capacity
  foreach e in P
    if (e in E) f(e) = f(e) + b # forward edge, up flow
    else f(e^R) = f(e) - b # forward edge, down flow
  return f
    
```

Mar 28, 2012

CSCI211 - Sprenkle

39

Intuition Behind Correctness of F-F Algorithm

- Let A be set of vertices *reachable* from s in residual graph at end of F-F alg execution
- By definition of A, $s \in A$
- By definition of the F-F algorithm's resulting flow, $t \notin A$


Mar 28, 2012

CSCI211 - Sprenkle

40

Ford-Fulkers

- What do we know about the flow out of A?
- What do we know about the flow into A?



Mar 28, 2012

CSCI211 - Sprenkle

41

This Week

- Problem Set 8 due Friday
- Start reading chapter 7

Mar 28, 2012

CSCI211 - Sprenkle

42